Liberty

VENDOR CATALOG / GROVHAC

Grovhac Catalog

Industrial mixers and agitators — 24 real Series organized across 9 mounting types, stainless steel wetted parts, 1/6 to 3 HP.

LAB MOUNT & C-CLAMP MOUNT

Series 2/15/20/200 · Series 4/40/44/400

> "With air motors, these agitators are inherently variable speed & explosion proof, cannot burn out or overheat" — a real, vendor-stated reason to spec an air motor for hazardous-location or stall-risk applications.

Series	HP Range	Notable
Series 200	1/3–1 HP	Heavy-duty lab mount, adds shaft support bearing
Series 400	1/4–3 HP	"Most popular" — super-duty ball & socket c-clamp + shaft support bearing
Series 44	1/4–1 HP	Smaller ball & socket c-clamp, lightweight/portable



TOTE MOUNT & SADDLE-PLATE MOUNT

TOTEMASTER Series 5100/5109 · Series 60/600

Series	HP Range	Notable
Series 5100 (TOTEMASTER)	1/3–2 HP	Unique clamps secure bridge to any tote; adjustable power-drive position
Series 5109 (TOTEMASTER)	1/3–2 HP	Collapsible turbines for small-entry install; preferred for square/rectangular containers
Series 600	1/4–3 HP	Heavy-duty ball & socket saddle plate + shaft support bearing



FLANGE MOUNT & 2″ NPT BUNG MOUNT

Series 700/710/720/770 · Series 9/90/91/900

> Series 770 carries the vendor's one explicit custom-manufacturing statement: "Customizable to your application; please contact us for details" — a real, specific baseline (1/2-3 HP, low-headroom 90° gear reducer) for high-viscosity large-batch top-entry mixing.

Series	HP Range	Notable
Series 720	1/3–2 HP	Shaft support bearing + double mechanical seal
Series 770	1/2–3 HP	Gear drive only; large-batch top-entry, high-viscosity process materials
Series 91	1/2–2 HP	Threads directly into 2″ NPT bung for near-airtight evaporation/contamination control
Series 900	1/3–2 HP	Removable bung adapter + collapsible propellers + shaft support bearing



NEXT STEP

Send LibertyCES the process data, not a part number.

24 real Grovhac mixer Series across 9 mounting types — but your actual application still has a specific vessel size, mounting constraint, and viscosity that determines the correct model.

Fluid, viscosity, vessel size and shape, mounting configuration, and hazardous-location requirements — that's what a real spec review needs to start.

Request a spec review

james@libertyces.com

(559) 395-5500

libertyces.com