

VENDOR CATALOG / NORWESCO

Norwesco Catalog

Rotationally molded, one-piece septic, cistern, holding, and vertical storage tanks — a TankHolding brand, since 1980.

BELOW GROUND TANKS

Septic, Bruiser, Legacy & Cistern Tanks

All Norwesco tanks are rotationally molded, one-piece, seamless construction. Real hard install constraint worth flagging on any quote: Legacy (ribbed) septic and cistern tanks must be kept full – or at least 1/4 full – at all times, or the tank can collapse under external soil pressure.



Legacy Septic Tank (Ribbed)

500–1500 gal

Rib design provides structural integrity. Cannot be used as pump tanks; must be kept full at all times. Lightweight enough to transport in a pickup, carried by 2 people.

Family	Capacity Range	Key Constraint
Low Profile Septic	500–1500 gal	Pumpable dry; also usable as pump tank or non-potable water
Bruiser Septic	1000–1500 gal	Also usable as holding tank, pump chamber, or potable water (single-compartment)
Legacy Septic (ribbed)	500–1500 gal	Must be kept full at all times
Spherical Pump Tanks	200–525 gal	May remain in ground when empty (unlike Legacy)
Holding Tanks	2000–10,000 gal	FDA-compliant resins; doubles as sewage tank per local code
Low Profile Cistern	575–1750 gal	ANSI/NSF Standard 61 certified where applicable
Legacy Cistern (ribbed)	600–1700 gal	600gal+ must be kept 1/4 full at all times

ABOVE GROUND TANKS

Vertical Storage – White/Natural & Black/Dark Green



Vertical Storage Tank – White/Natural

25–6,500 gal, 24 real sizes

Tie-down slots, built-in graduated gallonage indicators, offset fill-well, self-vented slosh-proof lids, installed bulkhead fitting standard.



Vertical Storage Tank – Black/Dark Green (and CA Green)

120–15,500 gal

Explicit water-only rating, verbatim from the catalog: "rated at 8 pounds per gallon...for WATER STORAGE ONLY! They should not be used for chemicals, fertilizers or any other product." Dark color limits light penetration to reduce algae growth.

Family	Capacity Range	Notable
Flat Bottom Utility	200–500 gal	Fits a pickup bed like PCO tanks
Pickup Truck Tanks	210–425 gal	Built-in gallon indicators, slosh-proof lids
Elliptical Leg Tank	3,135 gal	Lowest center of gravity for largest volume; requires 4 support bands
Freestanding Tanks	100–1,000 gal	Dimensioned to fit through a conventional doorway
Water Hauling Tanks	1,250–2,400 gal	Low-profile for height-limited vehicle/cabin placement

LIDS, FITTINGS & MANUFACTURING

Bulkhead Fittings, Lids & Warranty

Polypropylene bulkhead fittings, 1/2in through 4in, standard EPDM gasket with Viton offered as an option "when EPDM may not be suitable for your application" — an explicit vendor acknowledgment of EPDM's known compatibility limits with strong oxidizers like sodium hypochlorite.

Fitting	Tank Hole Size
1/2in Heavy Duty	1-7/16in
1-1/4in Anti-Vortex	2-1/4in
2in Self-Aligning	4-1/2in (installs above liquid level in tank dome)
2in Double Threaded 316SS	3-1/8in (ships less gasket)
4in Double Threaded	5-3/4in

Lids: 22", 16", 12", 8", 5" HDPE, vented/ventless, plus a hinged co-polymer lid opening a full 180° with a padlock-ready locking tab. Norwesco also sells poly welding gun and rod for on-site field repair of poly tanks.

Item	Detail
Manufacturing footprint	11 US sites + 1 Canadian (CA, GA, IA, MN, NY, OH x2, OK, TX, UT, WA; Edmonton AB)
Standard warranty	3-year from date of manufacture
Low Profile Tanks warranty	5-year (real upgrade over standard 3-year term)
TankHolding family	Norwesco, Snyder Industries, Ace Roto-Mold/Den Hartog — related brands, may share manufacturing capacity

NEXT STEP

Send LibertyCES the process data, not a part number.

Tank capacity, fitting, and warranty specs are real, but your actual application still has a specific fluid, install constraint, and local code requirement that determines the correct tank family and fitting material.

Fluid, capacity, install location, and local code — that's what a real spec review needs to start.

Request a spec review

james@libertyces.com

(559) 395-5500

libertyces.com