

## **2,000 Watt Inverter Computer Module Replacement**

This bulletin covers the following Champion Power Equipment models:

2,000 watt Champion Inverters – All Models

Note: Read instructions completely before performing service.

1. Remove handle bolts in four corner pockets with a 10mm socket.
2. Remove Phillips head screw inside of fuel knob and remove knob.
3. Remove gas cap and then lift top panel off. It will snap off easily. Remember to replace gas cap after top panel is removed. Be sure gas cap vent is in OFF position.
4. Remove three gas tank bolts on top with 7mm socket.
5. Lift gas tank up and hang over backside panel with hose connected.
6. Loosen plate bolt on end of module front side. Remove bolt and plate on end of module backside. Use a 10mm socket with extension.
7. Carefully depress lock tab on all white molex plug-ins on module and unplug.
8. Remove complete module from chassis, lifting upwards.
9. Reverse previous steps for installation of new module assembly.

NOTE – All plugs are unique except the two bottom ones. The red wire is plugged in closer to the edge of the control module. The brown wire is plugged in to the inner plug of the control module.

If you have any questions, please contact Champion Power Equipment:

Champion Power Equipment, Inc.  
12039 Smith Ave.  
Santa Fe Springs, CA 90670  
Phone: 1-877-338-0999

Email: [tech@championpowerequipment.com](mailto:tech@championpowerequipment.com)