

PROFESSIONAL REFRIGERATION FOR THE PERFECT



Elanpro's world class equipment has been developed over decades of painstakingly collected market research and customer experience. The Freezers and Refrigerators come with high quality components from Europe and are known for reliability and performance. They are designed to work under tough Indian condition. Elanpro machines can be found in Best Hotels, Bars, Restaurants, Pubs, Cafe's and QSR chains.



Salad, Prep & Under Counters - Static & Frost Free Series



Key Features:

- DANFOSS/EMBRACO compressor
- Dixell digital controller
- EBM Fan Motor
- Removable gasket
- Adjustable shelves
- Heavy duty lockable castors
- Lock
- Built in handle
- Environment Friendly Refrigerant
 - R134A for Chillers
 - R404A for Freezers



Common - All Models

- HACCP Compliance
- Adjustable Feet







Flexi Drawer Undercounter

CBR -2

Key Features:

- CFC Free Refrigerant
- User friendly controls with LED Temperature display
- Change drawer temperature from fridge to freezer at the touch of a button
- Auto energy saving hot gas defrost
- Removable gasket for easy cleaning
- GN 1/1 150 mm deep pan capacity maximizes available storage space
- Tropicalized to perform at $40^{\circ}\mathrm{C}$ ambient

Blast Chiller & Freezers



V-... F------

- CFC refrigerant and foam
- Complete structure interior 8
 exterior in stainless steel with round
 internal edges for easy cleaning
- Self closing doors with easy to clean and replace magnetic balloon gasket
- Replaceable Electric door mullion heater
- 75 mm thickness insulation for excellent thermal efficiency
- Ventilated refrigeration compartment
- Dixell controller and compact footprints
- Danfoss refrigeration components
- EBM Fan

Technical Specification - Reach-in, Salad & Prep Counters

Model	Description	Capacity (Ltrs)	Dimension (WxDxH) mm	Temperature Range	GN Compatibility	No. of Shelves	Climate Class	Inside SS
EGN 650 C2	2 Door Reach In Chiller	650	740 x 835 x 2010	-2°C ~ 8°C	2 x GN 1/1	3	43°C	SS 304
EGN 1410 C4	4 Door Reach In Chiller	1410	1480 x 835 x 2010	-2°C ~ 8°C	2 x GN 1/1	6	43º€	SS 304
EGN 650 F2	2 Door Reach In Freezer	650	740 x 835 x 2010	-10°C ~ -20°C	2 x GN 1/1	3	43°C	SS 304
EGN 1410 F4	4 Door Reach In Freezer	1410	1480 x 835 x 2010	-10°C ~ -20°C	2 x GN 1/1	6	43°C	SS 304
EGN 600 Fish®	Reach In Fish Chiller	600	680 x 810 x 2000	-2°C ~ 8°C	NA	5	40°C	SS 304
EGN 2100 C	2 Door Undercounter Chiller	265	1360 x 700 x 860	-2°C ~ 8°C	1 x GN 1/1	2	38°C	SS 304
EGN 3100 C	3 Door Undercounter Chiller	400	1795 x 700 x 860	-2°C ~ 8°C	1 x GN 1/1	3	38°C	SS 304
EGN 2100 F	2 Door Undercounter Freezer	265	1360 x 700 x 860	-10°C ~ -20°C	1 x GN 1/1	2	38°C	SS 304
EGN 3100 F	3 Door Undercounter Freezer	400	1795 x 700 x 860	-10°C ~ -20°C	1 x GN 1/1	3	38°C	SS 304
Frost Top 3F	Frost Top	NA	1102 x 678 x 430	-10°C	NA	NA	38℃	SS 304
EGN 3V	Ventilated Cooling Well	NA	1102 x 678 x 533	2°C ~ 8°C	3 x GN 1/1	NA	32°C	SS 304
EVRX 1200	Salad Display Counter	NA	1200 x 335 x 225	2°C ~ 8°C	5 x GN 1/4	NA	32°C	SS 304
EVRX 1400	Salad Display Counter	NA	1400 x 335 x 225	2°C ~ 8°C	6 x GN 1/4	NA	32°C	SS 304

Specifications, features and colours are subject to change without any notice, due to continuous product development.

Manufactured as per European Technology and Standards

GN Pan are optional

Technical Specification - Flexi Drawer Undercounter

Model	Description	Capacity (Ltrs)	Dimension (WxDxH) mm	Temperature Range	GN Compatibility
CBR 1-2	Flexi Drawer Counter	78	905 x 700 x 565	1°C ~ 4°C / -18°C ~ -21°C	2xGN 1/1
CBR 1-3	Flexi Drawer Counter	116	1230 x 700 x 565	1°C ~ 4°C / -18°C ~ -21°C	3xGN 1/1
CBR 2-2	Flexi Drawer Counter	179	905 x 700 x 830	1°C ~ 4°C / -18°C ~ -21°C	4xGN 1/1
CBR 2-3	Flexi Drawer Counter	262	1230 x 700 x 830	1°C ~ 4°C / -18°C ~ -71°C	6xGN 1/1

Manufactured as per European Technology and Standards GN Pan are optional

Technical Specification - Blast Chiller & Freezer

Model	Dimension (WxDxH) mm	Capacity Ltrs)	Cooling Capability#	Tray*	Power Supply	Cooling Mode
T3	660 x 650 x 430	39	8 kg / 5 kg	3	230 V / 50 Hz	Ventilated
D3	800 x 815 x 945	139	12 kg / 8 kg	3	230 V / 50 Hz	Ventilated
D5	800 x 815 x 1015	169	18 kg / 14 kg	5	230 V / 50 Hz	Ventilated
D10	800 x 815 x 1645	368	40 kg / 28 kg	10	230 V / 50 Hz	Ventilated
D14	800 x 815 x 2170	494	55 kg / 38 kg	14	380 V / 50 Hz	Ventilated

Specifications, features and colours are subject to change without any notice, due to continuous product development. #70/3°C in 90 minute #70/3°C in 90 minute #70/3°C in 90 minute.



Customer Care : +91-88823 02532 = Whatsapp Complain : +91-80108 03166 Email : care@elanpro.net = Email : enquiry@elanpro.net = Website : www.elanpro.net

E-Waste Helpline: 1800 2700 038, e-waste@elanpro.net