



# THE UNDISPUTED TANKLESS HEAVYWEIGHT

INDUSTRY LEADING EFFICIENCY AT 97%




## NCC300 DV / NCC300 OD

GQ-C5032WF-FF US

GQ-C5032WZ US

### SMALLER FOOTPRINT

Your space is incredibly valuable. The NCC300 occupies a smaller footprint allowing for seamless installation and reclaiming valuable space. Do more with less space.



33% less footprint than typical commercial installs.


### VERSATILITY

No matter your installation plans, the NCC300 is versatile enough to adapt with its small size, flexibility in venting material and termination location.




### GAS REBATES

Take advantage of the various rebates available when you choose one of our NCC300 models



### 20:1 TURN DOWN RATIO

The NCC300 is among the industry's best in turn down ratio. It also features a wide BTU range of 15 to 300k



NORITZ AMERICA CORP • 1-866-766-7489 • WWW.NORITZ.COM

MODEL	NCC300 DV	NCC300 OD
GQ Reference Number	GQ-C5032WZ-FF US	GQ-C5032WZ US
Vent Material	5" Stainless, 4" PVC / CPVC and PP	
Dimensions (inches)	18.9" (W) x 32.7" (H) x 14.2" (D)	
Weight (lbs)	108 lbs.	
Min. / Max. Btuh	15,000 - 300,000	
Thermal Efficiency	97%	
Temp. Settings	100-185°F	
Warranty	5-year warranty on heat exchanger, 5-year warranty on parts & 1-year reasonable labor	
Ultra Low NOx	Yes	
Remote Included	Yes	
Min. / Max. Flow Rate	0.5 GPM / 13.2 GPM	0.5 GPM / 13.2 GPM
Quick Connect	Yes	
High Altitude Approved	Up to 4,500 feet	
Wifi Compatible	Yes	



Commercial Energy Star Certified

# WIFI COMPATIBILITY



Stay on top of your unit's daily operation with our wifi adapter which allows you to troubleshoot and schedule maintenance alerts using our Noritz App.



# MULTI-UNIT CONTROL

QTY	MAX GPM	SC
2	26.4	QC-2
4	52.8	SC-401-6M
6	79.2	SC-401-6M
12	158.4	SCU-401-12M
24	316.8	SCU-401-24M

## MODEL NCC300 DV

