

NORITZ
TANKLESS WATER HEATERS

Next Gen True Commercial Tankless



NCC199CDV

GQ-C3260WZ-FF US

The new NCC199CDV provides industry leading performance for any commercial water heating application. An impressive 10-year heat exchanger warranty comes included, providing businesses with years of hot water without the worry.

Features

› 10 Year Heat Exchanger Warranty

The NCC199CDV is backed with a 10 year heat exchanger warranty. To learn more, visit www.noritz.com/cdvwarranty.

› 2" Vent Connections

Offers flexible venting options for vertical or horizontal termination with PVC, CPVC, or PP venting, as well as outdoor installations with OD vent cap. Ability to vent up to 65' with 2" and 150' with 3" materials.

› Pre-Mix Burner

Combined with a unique negative pressure Venturi gas valve, the NCC199CDV is energy star certified & features ultra-efficient 0.95 UEF.

› New Common Vent Capability

Provides scalability of up to 6 heaters on a single venting system without the need for an external non-return valve.

› Dual High Grade Stainless Steel Heat Exchangers

The right materials for the right situation. Utilizes 2 types of stainless steel: High temperature for the primary and corrosion resistant for the secondary.

› Ultra Low Nox

Produces only 14 ppm. 33% less emissions than the SCAQMD limitations of 20ppm NOx.



**Energy Star
Certified**



Common Venting Offers True Installation Flexibility

With Noritz Common Venting, up to 6 Noritz Water Heaters are able to share the same venting system. This means significantly reduced penetrations through the wall or roof -- resulting in less labor and a cleaner finished look. The use of a larger vent diameter system allows for longer vent runs for larger and taller buildings -- up to 200 ft. of equivalent vent length. The system is independently tested and approved for use by CSA in both the US and Canada. With the new built-in exhaust non-return valve, scalability of up to 6 heaters is possible now without an external non-return valve.

Technical Specifications

NCC199CDV		
Min. / Max. BTU	18K - 199,900 BTUh	
Capacity Range	0.5 - 11.1 GPM (30°F Rise)	
Weight	70 lbs.	
UEF	0.95	
Connection Sizes	Water Inlet	NPT 3/4"
	Hot Water Outlet	NPT 3/4"
	Gas Inlet	NPT 3/4"
	Condensate Drain	NPT 1/2"
Water Holding Capacity	0.82 Gallon (3.1 L)	
Temperature Settings	°F Mode	100-150° (In 5° F Intervals) 160° F, 170° F, 185° F (14 Options)
	°C Mode	37-48° C (In 1°C intervals), 50-85°C (In 5° intervals) (20 options)
Operating Pressure	15-150 psi (Recommended 50 to 80 psi for maximum performance)	
Included Accessories	Remote controller, remote controller cord, anchoring screws, wall mounting bracket	

TRUE Commercial Tankless

Trusted

Since 1951, Noritz's commitment and mission has been to "make people happy through hot water." With over 16,000,000 units serving people's hot water needs worldwide, our goal is to provide sustainable customer focused solutions for hot water.

Reliable

Noritz Commercial Tankless Water Heaters are modular and can be linked to create redundancy. Even when one unit needs service or is not in operation, hot water will be delivered seamlessly by other units in the system. Noritz redundancy in commercial applications provides a reliable, uninterrupted source of hot water which translates to piece of mind for our customers & their bottom line.

Unmatched

Noritz Commercial Tankless Water Heaters are the only TRUE commercial grade tankless water heaters on the market. Noritz continues to lead the industry in terms of innovation, quality, and performance. Noritz Intelligent Modular Water Heating Technology can link up to 24 units in a single system providing unmatched performance and reliability.

Efficient

For the rest of the pack, efficiency is a mere watermark to aim for. For Noritz, efficiency is our name. From an industry leading 0.95 UEF to the lean JPS just in time manufacturing process we utilize to manufacture our product.

Multisystem Control Superior commercial unit linking made easy				
Units Used	2	6	12	24
Accessory	QC-2	SC-401-6M	SCU-401-12M	SCU-401-24M

Additional Accessories



Commercial Wifi Adapter

The Noritz NWCC Commercial WiFi Adapter allows business owners and contractors to take full control of their tankless system.



System Controller (SC-XX)

Available system controller models can provide a central communication link for up to 6, 12, or 24 unit multi-systems.



Commercial Remote Controller

- Temperature adjustment from 100-185° (°C or °F)
- Recirculation Control Feature
- Time Stamps Error Codes



Quick Connect Cord (QC)

Provide simple staging and modulation for 2 units in small applications



Condensate Neutralizer Kit (NT20A)

Neutralize acidic condensate before it is dumped into common drains. Intended use: up to 3,000,000 BTU/hr or 5 GPH.