

HH HYBRID HOT SERIES

THE FIRST TANKLESS AND TANK COMBO FROM NORITZ. NOW WITH THE OUR LATEST NCC199CDV PRO.

The Hybrid Hot Series by Noritz brings together the storage of a standard tank with the power and efficiency of a tankless to take on any commercial hot water demand.

Combined to meet the hot water requirements of businesses, the Hybrid Hot Series by Noritz utilizes the latest in tankless and tank storage technologies to create a powerful and reliable solution for business owners. The Hybrid Hot also offers common venting for multiple units to ensure endless hot water is always available.



NORITZ NCC199CDV PRO

Our latest NCC199CDV Pro model now gives business owners even greater visibility and control of our award-winning commercial tankless. The new full function display allows for a faster initial setup, which minimizes downtime while also providing heater status, temperature controls, and more.

DEL SOL FOOD CO.
Brenham, TX

PANERA BREAD
Aurora, CO



NHH199100-2
Nominal Tank Capacity 119 Gallon
Tankless Capacity 199,900 BTUH

COMES WITH AN INDUSTRY-LEADING 10 YEAR WARRANTY

on both the storage tank and our NCC199CDV Pro tankless unit.

Noritz® is on the forefront of the tankless industry by pushing the limits of our technology to develop the most reliable and efficient products on the market. Combined with our world-class customer service, Noritz is the first choice in tankless water heating, giving installers peace of mind when choosing a tank replacement.



ASSEMBLED IN THE USA



SCAN TO WATCH OUR HYBRID HOT 3D EXPLAINER VIDEO

NORITZ

11160 Grace Avenue
Fountain Valley, CA 92708

Phone:
1-866-766-7489

Tech Support Hours:
Monday - Friday
5am - 6pm PST

Saturday
6am - 3pm PST

Follow us on social media
@NORITZAMERICA



09/2026 v2.5

NORITZ

HH HYBRID HOT SERIES BY NORITZ



THE BEST OF TANK + TANKLESS

OUR FIRST TANK AND TANKLESS COMBINATION SYSTEM

FEATURES

Meet the hot water demands of your business with confidence. The Hybrid Hot Series by Noritz® delivers faster hot water and provides up to 317 gallons per hour, making it an ideal solution for commercial applications with high and fluctuating demand.



EQUIPPED WITH OUR POWERFUL CDV PRO COMMERCIAL TANKLESS

Our Hybrid Hot now comes standard with our latest NCC199CDV Pro model which includes our upgraded control panel.



THE BEST OF BOTH TANK AND TANKLESS

With an endless supply of hot water, lower pressure drop, and no limitation of hot water flow rate, the Hybrid Hot combines features of both technologies to provide the most reliable hot water delivery system to date for commercial applications.



FASTER HOT WATER RECOVERY

The Hybrid Hot offers the best BTU possible at the quickest rate, providing businesses with energy savings and more. Thanks to its larger pump, hot water recovery speed with the Hybrid Hot is faster than other tank and tankless combinations.

For more information, visit us at
NORITZ.COM/HYBRIDHOT

NCC199CDV PRO

Our Hybrid Hot now utilizes our latest commercial tankless, the NCC199CDV Pro.

HOT WATER LINE

RECIRCULATION PUMP

TANK INLET PORT

T&P RELIEF VALVE

TANK OUTLET PORT

UPGRADED CONTROL PANEL

3/4 INCH GAS PORT

COLD WATER LINE

CEMENT LINING

With no anode rod and a greater warranty than other tanks on the market, our tank also features cement lining for superior corrosion resistance.

CONTINUOUS HOT WATER DELIVERY

If your tank suddenly runs out of hot water, no need to worry. The Hybrid Hot Series by Noritz® can continue to provide hot water using the paired NCC199CDV Pro tankless even after your stored supply is depleted*.

*Hot water capabilities are limited

ADDITIONAL FEATURES & BENEFITS

- ▶ Return water connection at tank mid-point for increased hot water production.
- ▶ Better vent sizing options over tank - 2 in. up to 65 ft.
- ▶ Common vent up to 12 units.
- ▶ Great for retro-fit or new applications.
- ▶ Easy maintenance for constant efficiencies over the life of the unit.
- ▶ Pre-installed dolly strap for easier and safer handling.
- ▶ Tighter thermostat temperature differential over tank for faster hot water recovery.
- ▶ Higher output temperature setting over conventional commercial tanks (100° F - 185° F).
- ▶ Competitively priced.

TECHNICAL SPECIFICATIONS

HYBRID HOT SERIES BY NORITZ®		
Product Number	NHH199100-2	
Installation Location	Indoor	
Appliance Type	NCC199CDV Pro (GQ-C3261WZ-FF-1 US) Tankless Water Heater paired with Insulated Storage Tank, Pump, and Controller	
Weight	536 lbs (Product Weight) 642 lbs (Shipping Weight)	
Working Pressure	Water	15 - 150 psi
	Gas	NG: 3.5 - 10.5" LP: 8.0 - 13.0"
Connection Size	Cold Water	NPT 1 1/2"
	Hot Water	NPT 1 1/2"
	Return (Recirc)	NPT 3/4"
	Gas	NPT 3/4"
Vent	Type	DV / SV
	Size	2" / 3"
	Max Length	2": 75' / 3": 150'
	Common Vent	Yes (Up to 12 Units)
Dimensions	H: 67 3/4" W: 28" D: 41.2"	
Power Supply	120 VAC (60Hz)	
Tank Capacity	119 Gallons (Cement Lined)	
Min. / Max. BTUh	12,800 - 199,900 BTUh	
Water Temperature Setting	100 - 185°F (37 - 85° C)	

PERFORMANCE

Approved Gas Types	Natural Gas or Propane
Efficiency	0.98 UEF (For NCC199CDV Pro tankless only)
AHRF CERTIFIED™	96% Thermal Efficiency (For system)
First Hour Rating	317 GPH

RECOVERY CAPACITY

PRODUCT NUMBER	APPROX. TANK CAPACITY	MAX INPUT (BTU/HR)	GPH VS TEMPERATURE RISE											
			30°F	40°F	50°F	60°F	70°F	80°F	90°F	100°F	110°F	120°F	130°F	140°F
NHH199100-2	119 Gal	199,900	780	585	468	390	334	292	260	234	213	195	180	167

