
Topology based naming method (Consistent Identification of Elements in Procedural Solid Modelling)


Ikjune Kim

2013/11/05

Persistent naming


- Persistent naming:
 - The naming of shape entity internally created during the modeling process
 - To record user selected entity in the procedural modeling
 - One of the problems of the procedural modeling






Naming method?

• A similar example of the map system




London Tube

An example of topological naming system



Geometry based Persistent naming


- Identification based on geometry
 - As is method in ISO 10303-55




Basic naming using the entity type and coordinate

Topology based Persistent naming


- Identification based on topology
 - Proposed naming method
 - Profile sketch information and feature creation type(extrude path)



- Face name is the basis name.
 - Edge and vertex name is determined by face name



Topology based naming



Naming method of CATIA V5R18

Edge name based on two adjacent faces in CATIA system

```
Set reference31 =
part1.CreateReferenceFromBRepName("REdge:(Edge:(
Face:(Brp:(Pad.1;0:(Brp:(Sketch.1;6)));

AllPartiallySharedIncluded:
(Brp:(Pocket.2;0:(Brp:(Sketch.3;5)));

Brp:(Pad.1;2);

Brp:(Pad.1;0:(Brp:(Sketch.1;4)));


Brp:(Pocket.1;0:(Brp:(Sketch.2;5)));Cf11:());

Face:(Brp:(Pad.1;2);

None:();Cf11:());


None:(Limits1:();Limits2:());Cf11:());WithTemporaryBody;WithoutBuild

Error;WithSelectingFeatureSupport;MFBRepVersion_CXR15)",
pocket2)
```




Ambiguity solving

- We use Object space information
 - Split face information
 - Merged face information
- Difference in PSI (parametric space information) among CAD systems




Standardization




Available features


Topology based naming method supports:



Selecting based on topology name



Basic naming method



Ambiguity solving

