

Attachment 2: Diamond drilling results 2025 from Ukkolanvaara, Karelian Gold Line, Finland

Hole ID	Easting	Northing	Elevation	Azimuth (°)	Dip (°)	Length (m)	From (m)	To (m)	Downhole length (m)	Au (g/t)
UKKO-001	717378.8	6976025.3	170.1	229.5	-45.1	179.60	3.35	9.65	6.30	2.67
						<i>including</i>	5.00	6.20	1.20	9.90
							16.20	36.20	20.00	1.60
						<i>including</i>	18.95	20.70	1.75	5.52
						<i>and</i>	26.9	29.95	3.05	4.07
							45.55	76.50	30.95	3.28
						<i>Including</i>	48.45	57.80	9.35	7.08
							97.90	98.75	0.85	1.62
UKKO-002	717455.3	6976086.4	169.8	229.7	-45.2	220.80	53.10	54.00	0.90	0.47
							110.65	136.90	26.25	1.89
						<i>Including</i>	116.70	123.70	7.00	4.53
						<i>and</i>	132.90	133.80	0.90	6.17
							144.15	162.80	18.65	1.75
						<i>Including</i>	149.15	150.15	1.00	7.50
						<i>and</i>	159.50	160.60	1.10	6.31
							192.15	204.95	12.80	1.48
UKKO-003	717534.4	6976145.8	169.9	230.1	-45.2	469.65	154.30	155.35	1.05	1.27
							232.60	244.85	12.25	0.77
						<i>Including</i>	232.60	234.60	2.00	2.58
						<i>and</i>	238.05	239.25	1.20	1.86
							250.00	259.10	9.10	4.72
						<i>Including</i>	255.55	256.40	0.85	17.90
							279.00	280.80	1.80	4.17
							355.35	356.55	1.20	0.54
UKKO-004	717615.2	6976208.0	170.1	230.0	-45.2	167.30	106.95	108.00	1.05	0.99
							113.70	114.70	1.00	0.43
							122.70	123.50	0.80	0.40
							124.50	125.55	1.05	0.71
							138.20	139.10	0.90	0.49
UKKO-005	717360.5	6976392.6	170.6	229.6	-45.1	273.40	15.80	21.85	6.05	0.76
						<i>Including</i>	18.00	19.05	1.05	1.84
							223.80	240.50	16.70	1.26
						<i>Including</i>	226.75	230.70	3.95	3.71
							244.85	246.05	1.20	0.44
							258.10	263.90	5.80	1.23
UKKO-006	717435.2	6976450.1	171.7	230.1	-45.0	211.70	39.65	40.55	0.90	7.09
							82.05	87.05	5.00	0.62
						<i>Including</i>	83.10	83.90	0.80	1.48
UKKO-007	717508.5	6976507.4	170.2	230.3	-45.1	212.10	No significant intersection			
UKKO-008	717170.0	6975861.2	169.3	50.0	-45.2	199.90	91.70	96.15	4.45	0.31
							124.30	125.25	0.95	0.86
							143.70	144.55	0.85	0.79
							177.30	178.40	1.10	1.14
UKKO-009	717138.0	6976197.3	170.2	50.0	-48.0	200.00	163.95	165.10	1.15	0.65
							178.25	182.80	4.55	1.94

							<i>Including</i>	179.10	180.10	1.00	5.44
								188.20	189.05	0.85	0.64
UKKO-010	717483.1	6976209.6	170.6	230.2	-45.1	409.70		150.10	151.00	0.90	0.94
								188.00	190.35	2.35	1.19
								209.90	210.95	1.05	1.80
								220.30	224.65	4.35	1.21
							<i>Including</i>	220.30	221.45	1.15	2.43
								258.70	264.80	6.10	0.48
							<i>Including</i>	263.15	263.95	0.80	1.44
								372.90	383.70	10.80	0.35
							<i>Including</i>	382.90	383.70	0.80	0.84
UKKO-011	717492.9	6976014.4	169.9	230.0	-45.2	408.60		59.10	60.10	1.00	0.44
								67.05	68.05	1.00	0.42
								82.70	83.75	1.05	0.57
								147.15	148.20	1.05	4.01
								235.10	236.80	1.70	0.51
								253.60	254.85	1.25	0.61
								333.50	334.30	0.80	0.70
UKKO-012	717564.3	6976077.3	170.0	230.2	-45.1	299.40		117.90	123.50	5.60	1.16
							<i>Including</i>	117.90	119.00	1.10	2.72
								212.90	216.10	3.20	0.68
								280.35	283.45	3.10	1.66
							<i>Including</i>	280.35	281.45	1.10	3.42
UKKO-013	717115.4	6976263.6	170.6	50.4	-50.1	271.80	<i>No significant intersection</i>				
UKKO-014	717682.3	6976264.7	169.9	230.1	-50.1	298.80	<i>No significant intersection</i>				
UKKO-015	717423.3	6975955.0	170.5	229.8	-45.1	311.30		67.10	70.85	3.75	2.02
	<i>Planned coord.</i>						<i>Including</i>	68.10	68.90	0.80	4.58
								83.20	85.10	1.90	3.52
								118.35	123.95	5.60	0.50
							<i>Including</i>	122.95	123.95	1.00	1.41
								249.70	250.80	1.10	0.97
								257.05	258.15	1.10	0.78
UKKO-016	717470.1	6975895.2	170.4	230.4	-45.2	310.90		20.15	21.05	0.90	0.53
	<i>Planned coord.</i>							80.90	87.10	6.20	2.93
							<i>Including</i>	80.90	82.00	1.10	9.36
								93.25	98.70	5.45	2.88
								118.40	119.50	1.10	0.49
								124.70	128.60	3.90	0.73
							<i>Including</i>	124.70	125.60	0.90	1.51
								169.30	170.25	0.95	0.64
UKKO-017	717542.9	6975959.4	171.2	229.9	-46.0	401.00		48.70	49.80	1.10	0.43
	<i>Planned coord.</i>							68.50	69.45	0.95	0.44
								162.55	163.65	1.10	0.45
								358.10	359.10	1.00	0.42

Note: A lower cut-off of 0.4 g/t Au and a maximum 5 m consecutive internal dilution was used for reporting. No upper cut-off grade was applied, and all figures were rounded up. True widths are not yet determined. Planned coordinates for UKKO-015, UKKO-016 and UKKO-017. Definitive collar locations will be measured by a surveyor at the end of the drilling program