







Replaces

1 of 3 Page



Sanitary tapware; Single taps and mixer taps

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Hansa Armaturen GmbH

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K652 "Sanitary tapware; Single taps and mixer taps" dated 10-10-2018.

which covers the requirements of

NEN-EN200:2008 "Sanitary tapware - Single taps and combination taps (PN10)".

Ronald Karel

Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273

Postbus 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 88 998 44 00 Fax +31 88 998 44 20

info@kiwa.nl

www.kiwa.nl

Company

Hansa Armaturen GmbH

Sigmaringer Straße 107

D-70567 STUTTGART

Duitsland

Tel. (+49) 711 1614-0

Fax. (+49) 711 161490196

info@hansa.de

www.hansa.de

Certification process consists of initial and regular assessment of:

- quality system
- product

page 2 of 3

Sanitary tapware; Single taps and mixer taps

Technical specification

The products mentioned below belong to this certificate:

Hansanova Style

Pillar tap, horizontal mounted, 131 mm outlet
Pillar tap, horizontal mounted, 94 mm outlet
Pillar tap, vertical mounted, 107 mm outlet
Pillar tap, vertical mounted, 126-186 mm outlet

Hansamedipro

0198 Pillar tap, horizontal mounted, 97 mm outlet

Remark

The above listed products were not yet assessed for compliance with all Hygienic Aspects as stated in the Dutch Drinking Water Decree and as outlined in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Regulation on materials and chemicals in drinking water and warm tap water supply), implemented on 19 July 2011, as specified in clause 4.2 of the Kiwa Evaluation guideline BRL-K652/05.

page 3 of 3

Sanitary tapware; Single taps and mixer taps

Application and use

The single taps and mixer taps are designed for application within the following limits of use:

- working pressure of maximum 1000 kPa;
- water temperature of maximum 90°C.

The recommended limits for correct operation are:

- working pressure of 100 kPa up to 500 kPa;
- water temperature of maximum 65°C

Marking

The Kiwa®-mark products are marked with the word mark "KIWA".

Place of the mark:

· on the body.

Compulsory specifications:

- name or mark of the manufacturer: on the body;
- indication of the acoustic group, if classified: on the body;
- indication of the flow rate class, if classified: on the body;
- indication for temperature selection.

Method of marking:

- · non-erasable;
- · visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Hansa Armaturen GmbH
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.