



# Materials Declaration

Product: Oras Electra  
Product name: Shower panel, 12 V  
Model number: 6662FTW  
SCIP Number (ECHA): a69f1275-5588-49a9-a505-1e44db4968de  
Weight: 8.157 Kg ( including package: 9.896 Kg )

| Materials (product):                    | Weight   | %       |
|-----------------------------------------|----------|---------|
| Aluminium (Al)                          | 3972.0 g | 48.70 % |
| Brass                                   | 2673.6 g | 32.78 % |
| PVC (Polyvinyl Chloride)                | 559.8 g  | 6.86 %  |
| ABS (Acrylonitrile Butadiene Styrene)   | 335.8 g  | 4.12 %  |
| Stainless steel (AISI)                  | 201.9 g  | 2.48 %  |
| POM (Polyoxymethylene)                  | 171.4 g  | 2.10 %  |
| Copper (Cu)                             | 66.9 g   | 0.82 %  |
| Softpex                                 | 62.4 g   | 0.77 %  |
| Svhc                                    | 26.1 g   | 0.32 %  |
| TPE (Thermoplastic Elastomer)           | 23.1 g   | 0.28 %  |
| PSU (Polysulfone)                       | 19.5 g   | 0.24 %  |
| Silicone                                | 15.8 g   | 0.19 %  |
| EPDM (Ethylene Propylene Diene Monomer) | 13.1 g   | 0.16 %  |
| PBT (Polybutylene Terephthalate)        | 13.0 g   | 0.16 %  |
| PSU, GF20 (Polysulfone)                 | 8.0 g    | 0.10 %  |
| Glue                                    | 2.5 g    | 0.03 %  |
| Nickel (Ni)                             | 2.0 g    | 0.02 %  |
| Bronze                                  | 2.0 g    | 0.02 %  |
| Grease                                  | 1.0 g    | 0.01 %  |
| Tin (Sn)                                | 0.8 g    | 0.01 %  |
| PA12 (Polyamide)                        | 0.8 g    | 0.01 %  |
| Chromium (Cr)                           | 0.5 g    | 0.01 %  |

|                               |          |          |
|-------------------------------|----------|----------|
| Materials (package):          |          |          |
| Corrugated board, Paper fibre | 1650.0 g | 16.67 %  |
| Paper                         | 71.6 g   | 0.72 %   |
| PE (Polyethylene)             | 20.9 g   | 0.21 %   |
| PA (Polyamide)                | 5.8 g    | 0.06 %   |
| Cellulose fiber               | 2.0 g    | 0.02 %   |
| Sharp Tear                    | 0.2 g    | < 0.01 % |

16.12.2024  
Jukka Hokkanen  
Manager, Material technology

