



JBM CAMPLLONG, S.L.

CERTIFICADO DE CONFORMIDAD CE

CONCEPTO: Conformidad CE para Equipos de Taller
Producto: Pistola de Impacto de ½" Mini Composite
Artículo nombrado por el fabricante: SM-43-4012P

Importado por: JBM CAMPLLONG, S.L.
Distribuido por: JBM CAMPLLONG, S.L.
Dirección: CIM La Selva – Crta. Aeroport Km 1.6 Nave 2.2, 17185 Vilobí d'Onyar
CIF: B17419292

Detalles del producto:
Referencia del distribuidor: 51206
Alimentación: Neumática
Conformidad con los estándares EN ISO 12100:2010, EN ISO 11148-6:2012, EN ISO 28927-2:2009, EN ISO15744:2008 y las normativas 2006/42/EC



EC DECLARATION OF CONFORMITY

We,

declares under our sole responsibility that the product to which this declaration relates, is in conformity with the requirements of New Machinery Directive 2006/42/EC on the approximation of the laws of the Member States relating to the safety of machinery.

Type: 51206_SM-43-4012P 1/2" Mini Impact Wrench – Twin Hammer

National Standards Applied:

1. EN ISO 12100: 2010 (Risk Assessment & Risk Reduction)
2. EN ISO 11148-6: 2012 (Safety Requirements)
3. EN ISO 28927-2: 2009 (Vibration level)
4. EN ISO15744: 2008 (Noise level)

Technical Data: Free speed: 11,000 rpm
Anvil Size: 1/2"
Loosening Torque: 1,302 Nm (960 Ft-lbs)
Max. Torque 624 Nm (460 Ft-lbs)
Working Torque Range: 34~ 338 Nm (25~250 ft-lbs)
Air Inlet: 1/4"
Hose Size (ID): 3/8" (10mm)
Air Pressure 90 psi (6.2 bar)
Air Consumption 4 cfm
Length: 6" (153 mm)
Weight: 2.6 lbs (1.2 kgs)

Tool Data: This tool produces a noise level (no load) of 82.5 dBA sound pressure and 93.5 dBA, & Sound power noise level (with load) of 95.6 dBA sound pressure and 106.6 dBA sound power per EN ISO15744:2008.

Vibration level is 7.4 m/s² Tested per EN ISO 28927-2, the uncertainty, K=1.43 m/s².



Signature of Issuer: _____

Name & Position of Issuer: Lung-Pao Chen, Plant Manager
Date & Place of Issue: July 09, 2018