



## EU DECLARATION OF CONFORMITY

Distributed by: JBM CAMPLLONG, S.L.U.

Address: CIM La Selva – Crta. Aeroport Km 1.6 Nave 2.2, 17185 Vilobí d’Onyar, Girona

CIF: ESB17419292

Product’s description: MINI AIR IMPACT WRENCH 1/2" COMPOSITE

Manufacturer’s reference: SM-43-4012P

Distributor’s reference: 51206

The declaration object complies with the directive 2006/42/EC; and the following standards:

Standard	Title	Edition/ Date
EN ISO 12100	Safety of machinery- General principles for design - Risk assessment and risk reduction.	2010
EN ISO 11148-6	Hand-held non-electric power tools – Safety requirements – Part 6: Assembly power tools for threaded fasteners.	2012
EN ISO 28927-2	Hand-held power tools – Test methods for evaluation of vibration emission – Part 2: Wrenches, nutrunners and screwdrivers.	2009
EN ISO 15744	Hand-held non-electric power tools – Noise measurement code – Engineering method	2008

Signed by:



Eduard Godoy

Purchasing department director

Girona, 9th of August, 2021

---

## EC DECLARATION OF CONFORMITY

---

We,

declares under our sole responsibility that the product to which this declaration relates, is in conformity with the requirements of New Machinery Directive 2006/42/EC on the approximation of the laws of the Member States relating to the safety of machinery.

**Type: 51206\_SM-43-4012P 1/2" Mini Impact Wrench – Twin Hammer**

National Standards Applied:

1. EN ISO 12100: 2010 (Risk Assessment & Risk Reduction)
2. EN ISO 11148-6: 2012 (Safety Requirements)
3. EN ISO 28927-2: 2009 (Vibration level)
4. EN ISO15744: 2008 (Noise level)

**Technical Data:** Free speed: 11,000 rpm  
Anvil Size: 1/2"  
Loosening Torque: 1,302 Nm (960 Ft-lbs)  
Max. Torque 624 Nm (460 Ft-lbs)  
Working Torque Range: 34~ 338 Nm (25~250 ft-lbs)  
Air Inlet: 1/4"  
Hose Size (ID): 3/8" (10mm)  
Air Pressure 90 psi (6.2 bar)  
Air Consumption 4 cfm  
Length: 6" (153 mm)  
Weight: 2.6 lbs (1.2 kgs)

**Tool Data:** This tool produces a noise level (no load) of 82.5 dBA sound pressure and 93.5 dBA, & Sound power noise level (with load) of 95.6 dBA sound pressure and 106.6 dBA sound power per EN ISO15744:2008.  
Vibration level is 7.4 m/s<sup>2</sup> Tested per EN ISO 28927-2, the uncertainty, K=1.43 m/s<sup>2</sup>.



Signature of Issuer: \_\_\_\_\_

Name & Position of Issuer: Lung-Pao Chen, Plant Manager  
Date & Place of Issue: July 09, 2018