



CERTIFICADO GS

Distribuidor: JBM CAMPLLONG, S.L.U.

Dirección: CIM La Selva – Crta. Aeroport Km 1.6 Nave 2.2, 17185 Vilobí d'Onyar, Girona

CIF: B17419292

Descripción del producto: LLAVE DINAMOMÉTRICA DE 1/4"

Referencia del fabricante: ¼-25Nm

Referencia del distribuidor: 51262

El objeto de la declaración es conforme a la Ley de Seguridad de Productos Alemana (ProdSG).

Tests conforme a EK5/AK2 13-02.3:2018, AfPS GS 2016:01 PAK

Firmado:


JBM CAMPLLONG, S.L.U.
CIM LA SELVA - Crta. de l'Aeroport Km. 1.6 Nau 2.2
17185 VILLOBI D'ONYAR
GIRONA - SPAIN
Tel. 972 24 55 33 - Fax +34 972 24 54 37

Eduard Godoy

Director departamento de compras


En Girona, a 26 de enero de 2024



CERTIFICATE

No. Z1A 112238 0002 Rev. 00

Holder of Certificate:



Certification Mark:



Product:

**Torque screwdriver and spanner
Torque wrench**

Tested according to:

EK5/AK2 13-02.3:2018
AfPS GS 2019:01 PAK

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.:

704352100101-00

Valid until:

2026-10-21

Date,

2021-10-22


(Junjie (Steven) Xu)



Product Service

CERTIFICATE

No. Z1A 112238 0002 Rev. 00

Model(s): 1/4-6Nm, 1/4-25Nm, 3/8-60Nm,
3/8-120Nm, 1/2-220Nm, 1/2-330Nm

Parameters:

Model:	1/4-6Nm	1/4-25Nm	3/8-60Nm
Type:	Type II, Class A	Type II, Class A	Type II, Class A
Torque range (Nm)	1~6	5~25	10~60
Driving square nominal size (mm):	6.3	6.3	10.0
Net weight (g):	315	364	511
Model:	3/8-120Nm	1/2-220Nm	1/2-330Nm
Type:	Type II, Class A	Type II, Class A	Type II, Class A
Torque range (Nm)	20~120	40~220	60~330
Driving square nominal size (mm):	10.0	12.5	12.5
Net weight (g):	968	1303	1396