

52521

FICHA TÉCNICA

JBM



AC 1000V  
IEC 60900:2004

CONJUNTO DE 50 CHAVES  
ISOLADAS ATÉ 1.000V

1,43 6 240



Material: CR-V



50  
PCS

CrV



CONTÉM

|  |    |   |
|--|----|---|
|  | x3 | M4x4.0, M5x5.0, M6x5.0  |
|  | x4 | 4, 6, 8, 10mm   |
|  | x2 | R1, R2  |
|  | x2 | 6.3 x 89, 8.1 x 89  |
|  | x3 | PH0, PH1, PH2   |
|  | x7 | SL0.4x2.0, SL0.4x2.5, SL0.5x3.0, SL0.6x3.5, SL0.8x4.0, SL1.0x5.5, SL1.2x6.5mm |
|  | x3 | PZ0, PZ1, PZ2   |
|  | x9 | T6, T8, T9, T10, T15, T20, T25, T27, T30                                      |

|  |    |  |
|--|----|--|
|  | x5 | H2.5, H3, H4, H5, H6                           |
|  | x2 | R1, R2   |
|  | x4 | 1, 2, 3, 4                                     |
|  | x4 | 4, 6, 8, 10                                    |
|  | x1 | 89   |
|  | x1 | 89   |
|  |    | Voltage Tester:<br>3.0 x 70 +<br>Torx 31 x 105 |



JBM

www.jbmcamp.com

JBM