

ref. **53786**

PORTABLE OZONE GENERATOR

5000 MG/H (220V)

Function

- Effectively eliminates the smells, smoke, pollen, dust, dust mites and mold.
- Disinfects the air oxidizing viruses, bacteria, and organic and inorganic compounds.
- Sterilizes rooms with a lack of ventilation.

Advantages

- Light, convenient and powerful.
- Low noise level.
- Heat dissipater to prevent an overheating of the ozone plate.
- Stainless steel prefilter to prevent the emergence of big particles.
- Interior components and fan certified by UL (Underwriters Laboratories).

Technical specifications

Power	67W
Voltage	110V – 230V
Air volume treated	80 CFM (2,24m³/min)
Ozone output	5000mg/h
Noise level	45Db
Maximum disinfection volume	500m³
Working time for 500m ³	120min
Timer	Included – 2h
Dilution System	Fan (certified by laboratory UL)

Quality standards: EN 60335-1:2012+A11:2014+A3:2017, EN 60335-2-65:2003+A1:2008+A11:2012



Physical characteristics

Material	Aluminum and iron with powder coating
Dimensions	187x172x158mm
Weight	2.30kg

Working time according to the room volume

Room volume	Working time required
50m ³	20min
100m ³	40min
150m ³	60min
200m ³	80min
300m ³	100min
500m ³	120min

Date of issue: 15/05/2020