

ref. **54050**

TRANSMISSION OIL EXCHANGE AND FLUSHING MACHINE

Function

This product is used to remove, clean and replace fluid from most types and models of automatic gearboxes, transmissions, hydraulic torque transmissions, gearbox radiators and radiation pipelines.

Advantages

- ✓ Includes a variety of adapters
- ✓ Compatible with Audi, BMW, Ford, Volkswagen, Toyota, Land Rover, Buick vehicles



Technical specifications

Weight	58.97kg
Dimension	55x42x100cm
Power Source	12V (car battery)
Pump Power	70W
Oil Pressure Gauge Diameter	70mm
Oil Pressure Gauge range	0-10 bar (0-150psi)
Pressure Gauges	Both 2-3/4 (dia.) inches; 0~100 PSI, 20 PSI increments; 0~7 Bar, in 1 and 1/10 Bar increments
Fresh Oil Tank Capacity	30L
Used Oil Tank Capacity	30L
Filter	Auto Oil Filter, 4-3/4(L) x 3(dia.) inches; 17mm x 1.7 female threads
Oil Inlet and Return Hoses	3-(2x) 126 (L) x1/2(dia.) inches (1-red, 1-black) (1) 137(L) x1/2(dia.) inches (red); All with male and female quick couplers, 300 PSL (max.) rated

Contains

	Colour	Length	Diameter	Pressure
Connecting hose with quick coupler	Red	250mm	12,5mm (1/2")	max. 20 bar (300 psi)
Connecting hose with quick coupler	Black	250mm	12,5 mm (1/2")	max. 20 bar (300 psi)
Exchange and flushing device (x1)				
Adapter set with 37 connecting adapters/hose adapters (x1)				
12V battery clamps				