

54973

PROFESSIONAL 2-POST LIFT 380V - 4000KG

TECHNICAL SPECIFICATIONS

Voltage	380V / 50Hz / 16A
Power	2.2kW
Capacity of new oil tank	8L
Descent time (no load)	45s
Lifting time (no load)	<45s
Maximum load	4000Kg
Lifting height	1850mm
Weight	560Kg



SUMMARY

High-performance hydraulic lift, designed for automotive workshops and industrial facilities. It allows vehicles up to 4000 kg to be lifted with maximum safety and stability. Its ultra-low 11 mm platform makes it easy to load low-clearance cars, while the efficient hydraulic system ensures a lifting time of under 45 seconds. With quiet operation (<70 dB) and a robust structure, it is the ideal solution for demanding maintenance and repair tasks.

Key features:

- Load capacity: 4000 kg
- Ultra-low platform (11 mm) for easy access
- Maximum lifting height: 1850 mm
- Efficient hydraulic system with low noise
- Fast lifting and lowering (<45 s)
- Robust construction with 560 kg own weight
- Perfect for professional workshops and industries

54973**PROFESSIONAL 2-POST LIFT 380V - 4000KG****SUMMARY**

Technical specifications:

- Initial platform height: 11 mm
- Total height: 2824 mm
- Total width: 3420 mm
- Lifting time: < 45 s
- Lowering time: ≈ 45 s
- Hydraulic oil: 8 L (anti-wear hydraulic oil)
- Working temperature range: 5 °C – 40 °C
- Working humidity: 30 – 95 %
- Noise level: < 70 dB
- Storage temperature: -25 °C to 55 °C