Minimum Highway Design Standards

Whereas, It is in the public interest for the Town of Green Valley Shawano County to establish minimum highway design standards for highways being constructed in the town to accommodate anticipated traffic and afford satisfactory access to police, firefighting, snow removal, sanitation, and road maintenance equipment;

NOW THEREFORE IT IS HEREBY ORDAINED BY THE TOWN BOARD OF SUPERVISORS OF THE TOWN OF Green Valley Shawano COUNTY as follows:

SECTION 1. Definitions.

In order to clarify this ordinance the following definitions are applicable:

- A. Approach—that portion of road extending 100 feet on each side of a culvert or bridge.
- B. Base Course--the supporting base material of the roadway, including shoulder.
- C. Drainage—the gradual drying of highway by system of ditches, trenches, channels, etc.
- D. Grade--the rate of ascent or descent of roadway.
- E. Highway--the road or way over which the public generally has a right to pass, to include the complete right-of-way.
- F. Road Bed -- the whole material laid in place and ready for travel.
- G. Roadway -- the traveled portion of the highway.
- H. Surface 1/2-the top of the roadway, or traveled surface.

SECTION 2. Applicability.

This ordinance shall be applicable to all highways laid out by the Town Board after adoption of this ordinance, including any highways dedicated in plats for proposed subdivisions submitted for review pursuant to Chapter 236 of Wisconsin Statutes, any private highways being donated to the town, and any other highways being accepted by the town as public highways in the town.

SECTION 3. Minimum Road Design Standards.

The following minimum design standards shall apply under this ordinance: All town highways shall be classified as local roads unless designated by the town board as collector or arterial. The classification of all roads under this ordinance shall be within the complete discretion of the town board considering such factors as traffic count, character of anticipated traffic, and relation of highway to traffic paterns within the town and other highway systems. It is intended that local be the lowest traffic count, with access to private property as principal function. Collector highways are intended to be highways acting as collectors from local roads to higher priority roads or developed areas. Arterials are intended to serve as corridors through the town serving intra-regional and inter-area traffic movement.

		sidential ithout C/G*	Commercial/I With C/G*	Industrial Without C/G*
Minimum R.O.W.	661	66'	661	66°
Minimum width of Base)
Local	30'	28'	32'	321
Collector	321	32'	40'	501
Arterial	401	34'	40*	50'

With C/G means with curb/gutter Without C/G means without curb/gutter

Design Standards for Roads (Cont.)

		Roci	idential	Comme	rcial/Industria
Improvement		With C/G	Without C/G		Without C/G*
Zinp 201 Cincil C		112011 070	Machode of o	11211 070	William Of o
Minimum Width of	Surfa	cing			
Local		.30	20	32	24
Collector		32	22	40	30
Arterial		40	24	48	48
Maximum Grade (per	cent)			
		.* ·			
Local**		10	10	8	8.
Collector**		8	8	6	6
Arterial**		6	6	6	6
**Minimum Grade	.5				
Minimum Radius of	Hori	zontal Curv	e (in feet)		
Local		100	100	200	200
Collector		100	100	200	200
Arterial		300	300	400	400
Corner Radius at 1		sections			
		15	30	15	30
	**				

Minimum Length of Vertical Curve

--100', but not less than 20' for each algebriac difference in

Collector--200', but not less than 50' for each one percent Arterial --300', but not less than 50' for each algebriac difference in grade

Minimum	Length	of	Tangents	Between	Reverse	Curves

Local	. 100	. 100	200	200
Collector	100	100	200	200
Arterial	200	200	300	300
Minimum Sight Distance	(in feet)			
Local	200	200	200	200
Collector	250	250	250	250
Arterial	300	300	300	300

^{*}With curb/gutter--Without curb/gutter

Design Standards for Roads (Cont.)

	Res	idential	Comme	Commercial/Industrial		
Improvement	With C/G	Without C/G	With C/G	Without C/G*		
Design Speed (mile	s per hour)					
Local	30	30	30	30		
Collector	35	35	35	35		
Arterial	40	40	40	40		

CUL-DE-SACS (permanent)

Maximum Length

Maximum desirable length of roads with cul-de-sacs is 1,000 feet. Through roads are most desirable.

Minimum R.O.W. Radius at	Cul-de-sacs			
Local	60	60	60	60
Minimum Base Course Radi	us			
Local		42	40	42
Minimum Pavement Radius				
Local	40	40	40	40

Base Course

Base Course must be of a quality, thickness, and composition suitable for the location.

Surface Course

Surface Course must consist of either crushed aggregate or bituminous concrete composition suitable for anticipated traffic loads. The minimum amount of gravel necessary for acceptance must be at least 600 yards per mile. The minimum amount of pavement necessary for acceptance must be at least 2½" in thickness. (Note: These minimums may vary around the State and should be reviewed and established by each Town Board considering local conditions)

Ditching and Culverts

The ditching of the roadway must be complete and have proper elevation to provide for adequate drainage. Any culverts necessary for proper drainage shall be installed after elevation and location is obtained from the Town Board. The minimum length of any culvert installed in a road bed shall be at least two feet greater than the base course width. Apron end walls shall be used. The diameter and length will be subject to the approval of the Town Board, after the amount of the flowage is determined. In no case shall the culvert be less than 18" in diameter.

Design Standards for Roads (Cont.)

Bridges

All bridges shall meet the minimum requirements of state and federal law. In the event it is decided by the Town Board, that the construction of a bridge would be of a size and cost; that it would create a hardship to the owner of land, required to build said bridge, then the Town Board may proceed to accept the road, complete as required above, except that part extending 100 feet on each side of said bridge. This portion of the road shall be known as the approach. The approach will be accepted uncomplete, with the reversation that the town will bill back to the owner a portion of the cost of construction of such bridge. The Town will proceed to build said bridge and approach with the help of bridge aid if available, and billing the balance not covered by the aid or portion to be billed back to the owner.

SECTION 4. Authority for Higher Standards.

The road design standards in Section 3 as stated above are intended to be minimum design standards. The Town Board shall have the discretion to impose higher design standards where in the opinion of the Town Board local conditions require higher standards or anticipated traffic in quantity or quality will require higher standards.

SECTION 5. Application for Determination of Applicable Standards

Any person may apply to the town board to determine what design standards should apply in a particular location, giving the description of the proposed highway and proposed design standards being requested to be approved for any proposed highway being proposed to be built. No person shall commence construction of any highway anticipated to be turned over to the town without having written approval of the proposed highway design signed by the town board.

SECTION 6. Final Inspection and Acceptance by the Town Board.

Upon completion of the proposed highway, the Town Board will proceed to make final inspection, accepting or rejecting the highway as the case may be in the discretion of the Town Board. If the highway is rejected, then corrections must be made as stated by the Town Board before finals inspection will be made again. If final acceptance is made by the Town Board, the owner or owners will turn over to the Town, a warranty deed free and clear of any liens necessary to convey free and clear title to the town for the highway.

Adopted by the Town Board this 10 day of Movember , 1999

Filed in the Office of Town Clerk This _____ day of _____, 19_____



