## NOTICE

Over the last few weeks, the wastewater treatment plant has taken on a lot of Clearwater.

To help the system run smoothly, please do not connect your sump pump to the wastewater system. It is illegal to put Clearwater into the wastewater system.

## Reference:

SPS 321.17(3)(d)(7)(e): "The drain tiles or pipe that lead from the footing tiles to the sump pit shall be laid at a grade of at least 1/8 inch per foot leading to the sump pit. The remaining drain tiles or pipe shall be level or graded downward to the line leading to the sump pit.

- (e) Drain tile or pipe discharge.
  - 1. Drain tiles or pipe shall be connected to the sump pit.
  - **2.** The sump pit shall discharge to natural grade or be equipped with a pump.
  - **3.** All other aspects of drain tile discharge shall be in accordance with the uniform plumbing code, chs. SPS 382 to 387."

and SPS 382.36(4): "DISCHARGE, DISPERSAL, CLEARWATER REUSE OR STORMWATER USE.

- (a) Discharge points. The discharge points for stormwater and clearwater shall be as specified in Table 382.38-1. (b) Segregation of wastewater.
  - 1. Except as provided in subd. 2., stormwater or clearwater piping may not connect to a sanitary drain system.
  - **2.** Where a combined sanitary-storm sewer system is available, stormwater, clearwater and sanitary wastewater may be combined in the building sewer.
  - **3.** Stormwater gravity drains shall not be combined with clearwater drains prior to discharging to the storm building drain except where approved by the department."