TOWN OF WAUTOMA APPLICATION FOR PERMIT TO MAKE EXCAVATION OR FILL OR TO INSTALL CULVERT

Inasmuch as Chapter 86.07(2) of the Statutes states that "No person shall make any excavation or fill or install any culvert...in any highway...without a permit therefore from the highway authority undersigned request a permit for the purpose of:

On Township Road	located	miles (north-
south-east-west) of	_ junction with	a markina, and in the area.
in Town of Wautoma in Section of	Waushara County.	
Approximate starting date	·	
Approximate completion date	-	
APPLICANT SHALL PLACE A FLAG OR MA FROM THE HIGHWAY AT THE LOCATION		
A representative of the Wautoma Town Board Investigation and field inspection.	d in company with the applica	ant will make an
TO BE COMPLETED BY THE TOWN BOARD REPRESENTATIVE	Signed (Town Repres	entative)
Type of drivewayNCR, NCU, CR CU	Signed	Property Owner)
Add'l driveway? If so explain why	(Applicant / I	roporty Owner)
Number of driveways	(Print name pl Address	
Proposed land use	-	
Side of the road Quadrant		
If no culvert, state why	Phone # Mail this application t	o:
Date checked By		
Additional Clauses	W8674 Fawn Co Wautoma, WI	

ALL FENCES, TREES, SHRUBS AND/OR FIXTURES MUST BE OFF HIGHWAY RIGHT OF WAY

TYPE OF DRIVEWAY	NUMBER OF ACCESS DRIVEWAYS	WIDTH MAX./ MIN.
Commercial & Industrial Land Uses	2	50 / 24 feet
Residential Land Uses	1	15 /16 feet
Agricultural Land Uses On Class A and B Hwys	1 per parcel	50 / 24 feet
Agricultural Land Uses On Class C Hwys	No maximum number	50 / 24 feet

Conversion of an access point from one type of use to another shall be treated the same as Opening a new access point and must meet the conditions of these regulations.

Design Standards: Driveways to Class A and Class B highways must comply with the design Provisions of the access permit issued by the Wisconsin Department of Transportation of the County Highway Department. Driveways to Class C highways must comply with inspection And culvert requirements of the Town of Wautoma provided they meet the following minimum standards.

- 1. Culverts, if needed, must be a minimum of 15 inches.
- 2. Driveway height must not exceed the level of the outside edge of the road shoulder.
- 3. No end or retaining walls shall be permitted on driveways.
- 4. The side slopes of the driveway shall equal or be flatter that the side slope of the main highway but should not be steeper than 2 ½ to 1, unless otherwise designated on an individual basis.
- Concrete shall not be used for driveway surface material within the right of way of all State and County Highway and Township roads.