## TOWN OF QUINCY 18<sup>TH</sup> AVE. LRIP PROJECT 2025

**SCOPE OF WORK:** The work under this contract shall consist of full depth pulverizing existing pavement, grade and compact, the addition of 4 inches compacted limestone base 26 ft in width, fine grade, water and compact, pave 2.5 inches of hot mix asphalt, and placement of 3 ft shoulders using ¾ inch limestone base. Pavement width will be 20 ft wide.

PROJECT LIMITS: CTH F TO DOVER DRIVE.

CRUSHED AGGEREGATE BASE COURSE: 3/4 or 1 1/4 inch crushed limestone aggregate must meet Wisconsin DOT specifications.

HOT MIX ASPHALTIC PAVEMENT: The hot mix shall be 4LT 58-28s Mix. Mix will be placed at a compacted thickness of 2½ inches. Each driveway shall have a minimum 18-inch asphalt apron. All hard surface driveways shall be saw cut far enough back for an acceptable transition from roadway.

<u>SHOULDERS:</u> Shoulders shall be ¾ inch crushed limestone aggregate (meeting Wisconsin DOT Specifications.

**COMPLETION DATE:** SEPTEMBER 30<sup>TH</sup> 2025

**INSURANCE:** Workers Compensation \$100,000 Each accident

\$500,000 Disease policy limit

\$100,000 Disease each employee

Comprehensive Auto Liability \$1,000000 Combined Single Limit

Coverage to apply to all owned, hired and non-owned vehicles.

Comprehensive General Liability \$1,000,000 Per Occurrence

\$2,000,000 Aggregate

Excess/Umbrella Liability \$1,000,000 Per Occurrence

\$2,000,000 Aggregate

Excess/Umbrella Coverage to be excess over employer's liability automobile

liability and general liability. Include insurance with Bid.

The Town of Quincy, Adams County reserves the right to accept or reject any and all bids or accept the bid most advantageous to the Town.

This project will require an engineering certification of 10 year life or more expectancy on completion by the contractor to the Town.

Bids consist of one (1) General Contractor.

Note: All contractors use Bid Form and bid on quantities on the Form.

## TOWN OF QUINCY 18<sup>TH</sup> AVE. LRIP PROJECT BID FORM

## $18^{TH}$ AVE. – CTH F TO DOVER DRIVE (.47 MILES)

FULL DEPTH PULVERIZE ADD 4" OF 1 ¼ LIMSTONE BASE COMPACTED	1,584 TON	TOTAL =\$
PAVE 2 ½ INCH 4LT 58-28S HOT MIX MAT	792 TON	TOTAL = \$
SHOULDER 3FT USING ¾" LIMESTONE BASE	286 TON	TOTAL = \$
GRAND TOTAL \$		