

Nitrogen Generator *Infinity 50 Series*

Peak **Infinity.** beyond expectations.

Perpetual flow nitrogen generators Performance and value beyond expectations

The ***Infinity 50*** series delivers performance and value beyond expectations. Offering a pure and reliable source of gas, these perpetual flow Nitrogen generators are suitable for a variety of applications in your laboratory.

Expertly designed by Peak Scientific's knowledgeable Engineering team, the ***Infinity 50*** series will offer a single generator solution for multiple analytical instruments. We are proud to provide gas generators with superior performance and a 'world class' after market service as standard.

PEAK SCIENTIFIC. GO WITH THE FLOW.



PEAK[®]
SCIENTIFIC



Nitrogen Generator Infinity 50 Series

Features & Benefits:

Durable – Few moving parts with minimum maintenance requirements

Single Source Solution – one generator can cater for the requirements of multiple applications and multiple laboratories on site

Quiet – Completely silent in operation

Mobile – Flexibility to position generator where required, the generator is supplied with caster wheels for easy mobility

Simple Installation – Commission Peak Scientific's expert installation engineers, let us do the work for you

Economical – More cost effective than any other gas supply method

Convenient – Gas on demand, no health hazards, no need to worry about running out of gas

Eco-Friendly – Onsite gas generation considerably reduces your carbon footprint

Experience – preferred choice supplier of many instruments manufacturers

These Generators are designed to be connected to an existing air supply and can cater for the requirements of LCMS, LCMSMS, Sample Evaporators, ELSD and NMR applications.

Technical Specifications

	5010	5020	5030	5040	5050	5060	5070	5080
Nitrogen (L/min)	60	120	180	240	300	360	420	480
Inlet Air Requirement (L/min)	180	360	540	720	900	1080	1260	1440
Min/ Max Air Inlet Pressure	125-145 psi							
Min/ Max Operating Temperature	5°C (41°F) - 30°C (86°F)							
Particles	< 0.01 µm							
Suspended Liquids	None							
Phthalates	None							
Pressure Dewpoint	-40°C / 40°F							
Electrical Requirements	110 - 230v 50/60 Hz							
Dimensions (cm / ins) WxDxH	50 x 80 x 115 / 19.6 x 31.5 x 45.2							
Weight (kg / lbs)	70	75	80	85	90	95	100	105

Product Accreditations: 

Peak Scientific UK

Tel: +44 (0)141 812 8100
Fax: +44 (0)141 812 8200

Peak Scientific North America

Tel: +1 866 647 1649
Fax: +1 978 608 9503

For a full list of our worldwide office locations, please visit:

Web: www.peakscientific.com/contact



Peak Scientific's Quality Management System conforms to: ISO:9001:2008



Ordering Information

	5010	5020	5030	5040	5050	5060	5070	5080
Part Number	13-5010	13-5020	13-5030	13-5040	13-5050	13-5060	13-5070	13-5080
Annual Service Kit	08-0313				08-0314			

Standard Maintenance Plan 09-3110
Complete Maintenance Plan 09-3010

Website: www.peakscientific.com
Email: infinity@peakscientific.com