



»AUT 30«

The flexible machine with multifunctional infeed

The AUT 30 is the most flexible of the multipurpose dicers. Whether product is loaded by hand, with the integrated lift-tilt mechanism, or by means of conveyor belts, the AUT 30 adapts itself easily to any task with the appropriate infeed configuration. It can process loose or pre-formed products and blocks. Depending on application the machine can be configured to process meats as well.

Product features:

- » Fully sealed VAC product loading chamber with open drainages
- » Sidewall opening, can be adjusted to product size for loading
- » THC system*
- » High-speed hydraulics guarantee minimum loading times
- » Power-pack for products with high cutting resistance*
- » Speed-pack (adjustable blade speed)*
- » Fully automatic lubrication system
- » Computer controlled and touch screen
- » Product window in blade chamber
- » Integrated lift-tilt mechanism (optional)
- » Two-part grid
- » Hardened shear edges and product stabilisers
- » Simple and safe grid fixation
- » Intelligent automatic slice speed control

* Accessories



CE All machines fulfil the strictest CE safety and hygiene regulations.

Technical specifications	AUT 30	
Output (Depending on product)	Max. 2.800 kg/h	
Loading dimension W x H x L	120 x 120 x 550 mm	
Feed motion	1-40 mm	
Power supply	8,5 kW	
Weight	900 kg	
L x W x H	1.850 x 1.730 x 1.970 mm	
Cutting grid sizes	5 x 5 mm - 75 x 75 mm	