



- 750 litre bowl of stainless steel
- Almost completely made of solid stainless steel
- Operation via cross lever switches
- Separate digital control in stainless housing
- Ejector, main cover and noise absorbing cover hydraulically operated
- Main Cover of stainless steel
- Noise absorbing cover of transparent special plastic
- Closed machine bottom with ventilation system
- Many further options

AC-8	DC-8	Ultra	Rasant
<p>6 steplessly pre-programmable forward knife speeds</p> <p>2 reverse mixing speeds</p> <p>2 separate bowl speeds</p> <p>Frequency-controlled 3-phase motor of the main motor, max. 250 kW</p> <p>Separate 2 speed bowl drive motor</p> <p>Frequency-controlled drive system with smart control of output</p> <p>Command 1000 Digital display for gear, knife speeds, running time, temperature, bowl speeds, time. All knife speeds are steplessly pre-programmable according to the motor type variant and subsequently retrieved via the practical customer-orientated knee operation or cross operation of the Cutter. Switch-off automatic system for temperature and running time. Up to 9 switch-offs possible. Display of maintenance intervals and service intervals.</p> <p>Separate Panel box of stainless steel with built-in main-switch</p>	<p>6 steplessly pre-programmable forward knife speeds</p> <p>2 reverse mixing speeds</p> <p>2 separate bowl speeds</p> <p>3-phase motor, max. 250 kW</p> <p>Separate 2 speed bowl drive motor</p> <p>Command 1000 Digital display for gear, knife speeds, running time, temperature, bowl speeds, time. All knife speeds are steplessly pre-programmable according to the motor type variant and subsequently retrieved via the practical customer-orientated knee operation or cross operation of the Cutter. Switch-off automatic system for temperature and running time. Up to 9 switch-offs possible. Display of maintenance intervals and service intervals.</p> <p>Separate Panel box of stainless steel with built-in main-switch</p>	<p>2 knife speeds</p> <p>2 mixing speeds</p> <p>2 separate bowl speeds</p> <p>3-phase motor with 140, 160 or 190 kW</p> <p>Separate 2 speed bowl drive motor</p> <p>Command 1000 Digital display for gear, knife speeds, running time, temperature, bowl speeds, time. All knife speeds are steplessly pre-programmable according to the motor type variant and subsequently retrieved via the practical customer-orientated knee operation or cross operation of the Cutter. Switch-off automatic system for temperature and running time. Up to 9 switch-offs possible. Display of maintenance intervals and service intervals.</p> <p>Separate Panel box of stainless steel</p>	<p>2 knife speeds</p> <p>2 bowl speeds</p> <p>3-phase motor with 140, 160 or 190 kW</p> <p>Command 1000 Digital display for gear, knife speeds, running time, temperature, bowl speeds, time. All knife speeds are steplessly pre-programmable according to the motor type variant and subsequently retrieved via the practical customer-orientated knee operation or cross operation of the Cutter. Switch-off automatic system for temperature and running time. Up to 9 switch-offs possible. Display of maintenance intervals and service intervals.</p> <p>Separate Panel box of stainless steel</p>