



120 litre bowl of stainless steel

Almost completely made of solid stainless steel

Operation via knee lever switches (on request via cross lever switches)

Separate digital control in stainless housing

Noise absorbing cover of transparent special plastic

Closed machine bottom with ventilation system

Central point of lubrication for knife shaft

Balanceable and exchangeable knife head

Many further options

AC-8	Ultra	Rasant
<p>6 steplessly pre-programmable forward knife speeds</p> <p>2 reverse mixing speeds</p> <p>2 separate bowl speeds</p> <p>Frequency-controlled 3-phase motor of the main motor, max. 80 kW</p> <p>Separate 2 speed bowl drive motor</p> <p>Frequency-controlled drive system with smart control of output</p> <p>Command 1000: Digital display for gear, knife speeds, running time, temperature, bowl speeds, time. All knife speeds are steplessly pre-programmable according to the motor type variant and subsequently retrieved via the practical customer-orientated knee operation or cross operation of the Cutter. Switch-off automatic system for temperature and running time. Up to 9 switch-offs possible. Display of maintenance intervals and service intervals.</p> <p>Separate Panel box of stainless steel with built-in main-switch</p> <p>On request: Command 500 machine-mounted</p>	<p>2 knife speeds</p> <p>2 mixing speeds</p> <p>2 separate bowl speeds</p> <p>3-phase motor with 26, 32 or 45 kW</p> <p>Separate 2 speed bowl drive motor</p> <p>Command 1000: Digital display for gear, knife speeds, running time, temperature, bowl speeds, time. All knife speeds are steplessly pre-programmable according to the motor type variant and subsequently retrieved via the practical customer-orientated knee operation or cross operation of the Cutter. Switch-off automatic system for temperature and running time. Up to 9 switch-offs possible. Display of maintenance intervals and service intervals.</p> <p>Separate Panel box of stainless steel</p> <p>On request: Command 500 machine-mounted</p>	<p>2 knife speeds</p> <p>2 bowl speeds</p> <p>3-phase motor with 26, 32 or 45 kW</p> <p>Command 500: Microprocessor-controlled digital display for gear, rotation speed of knives, running period, temperature, bowl speed and time. According to the motor type variant knife speeds steplessly programmable to be activated at the cutter by the practice-oriented knee lever switch respectively by the cross switch. Switch-off automatic system for running time and temperature. Up to 9 switch-offs possible Different service displays and error displays. Display of maintenance intervals and service intervals.</p> <p>Separate Panel box of stainless steel</p>