Seydelmann



60 litre bowl of stainless steel

Cooking system

Almost completely made of solid stainless steel

Operation via cross lever switches

Separate digital control in stainless housing

Main cover of stainless steel, hydraulically operated

Noise absorbing cover of stainless steel, manually operated

Closed machine bottom with ventilation system

Central point of lubrication for knife shaft

Balanceable and exchangeable knife head

Many further options

AC-8	Ultra	Rasant
AC-8	Olita	Rasalit
6 steplessly pre-programmable forward knife speeds	2 knife speeds	2 knife speeds
2 reverse mixing speeds	2 mixing speeds	2 bowl speeds
2 separate bowl speeds	2 separate bowl speeds	3-phase motor with 12, 17 or 21 kW
Frequency-controlled 3-phase motor of the	3-phase motor with 12, 17 or 21 kW	Command 1000 Digital display for gear, knife speeds, running
main motor, max. 40 kW	Separate 2 speed bowl drive motor	time, temperature, bowl speeds, time.All knife speeds are steplessly pre-programmable
Separate 2 speed bowl drive motor	Command 1000 Digital display for gear, knife speeds, running	according to the motor type variant and subsequently retrieved via the practical
Frequency-controlled drive system with smart control of output	time, temperature, bowl speeds, time.All knife speeds are steplessly pre-programmable	customer-orientated knee operation or cross operation of the Cutter.
Command 1000	according to the motor type variant and subsequently retrieved via the practical	Switch-off automatic system for temperatureand running time.
Digital display for gear, knife speeds, running time, temperature, bowl speeds, time.All knife	customer-orientated knee operation or cross operation of the Cutter.	Up to 9 switch-offs possible. Display of maintenance intervals and service
speeds are steplessly pre-programmable according to the motor type variant and	Switch-off automatic system for temperatureand running time.	intervals.
subsequently retrieved via the practical customer-orientated knee operation or cross	Up to 9 switch-offs possible. Display of maintenance intervals and service	Separate Panel box of stainless steel
operation of the Cutter. Switch-off automatic system for	intervals.	
temperatureand running time. Up to 9 switch-offs possible.	Separate Panel box of stainless steel	
Display of maintenance intervals and service intervals.		
Separate Panel box of stainless steel with built-in main-switch		