

30



STEP LADDERS

Available in a wide variety of sizes and strengths for occasional, regular and intensive usage.

- 32 TB Davies HDUTY-S Aluminium Professional Swingback Step
- 33 TB Davies INSUL8-S Fibreglass Professional Swingback Step
- 34 TB Davies INSUL8-P Fibreglass Professional Platform Step
- 36 TB Davies PROBAT Aluminium Industrial Platform Step
- 38 TB Davies HDUTY-P Aluminium Professional Platform Step
- 39 TB Davies MAXI Aluminium Professional Platform Step
- 40 TB Davies PREMIER-XL Aluminium Trade Platform Step
- 41 TB Davies HORIZON Aluminium Trade Platform Step

Duraclimb Technology



Some of the products in this section use Duraclimb Technology Treads are secured by tough spun-rung Duraclimb technology, providing the strongest possible mechanical connection for intensive use.



NEXT DAY
DELIVERY



5-YEAR
WARRANTY



MAX LOAD
150 KG




INTENSIVE
USAGE

tb davies

TB Davies HDUTY-S Aluminium Professional Swingback Step

Ideal for all professional and commercial use. The TB Davies HDUTY-S Swingback Step Ladder replaces the Classic Class 1 Swingback Step. Our new and improved step ladder complies with EN131 Professional standards, so you can be assured that you are standing on a top-quality ladder product. The TB Davies HDUTY-S is a step ladder designed for hard work, day after day. They are manufactured using a heavy-duty aluminium box section with riveted 80mm deep treads, offering greater comfort on your feet. The heavy-duty locking stays keep your steps open securely and are easy to open and close. The back legs feature an extra-strength box section for maximum stability. They are complete with heavy-duty bracing on each leg — our best version yet of the Classic TB Davies Swingback Steps that will outlive the competition. With one of the broadest size ranges, from 4 to 10 treads, our TB Davies HDUTY-S Swingback Steps are available from our extensive customer network.

- Comfortable 85mm treads
- Heavy duty all aluminium construction
- Hinged metal locking stays provide optimal stability
- Box section with heavy-duty bracing
- Slip resistant feet provide a firm footing
- EN131 Professional



Large non-slip feet for maximum stability, ground connection

TB DAVIES HDUTY-S ALUMINIUM PROFESSIONAL SWINGBACK STEP

SKU	TREAD COUNT*	MAX STEP HEIGHT (M)	APPROX. WORKING HEIGHT†(M)	CLOSED HEIGHT (M)	WIDTH (M)	OPEN DEPTH (M)	WEIGHT (KG)
1200-024	4	0.22	1.97	0.98	0.42	0.69	3.9
1200-025	5	0.43	2.18	1.21	0.45	0.86	4.6
1200-026	6	0.64	2.39	1.44	0.47	1.01	5.5
1200-028	8	1.06	2.81	1.90	0.53	1.34	7.3
1200-030	10	1.48	3.23	2.36	0.58	1.67	8.9

Where applicable, Approx. Working Height[†], is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.

*Tread count includes top platform step.

†Heavy Item - 2-person lift required.



Swingback



NEXT DAY
DELIVERY



3-YEAR
WARRANTY



MAX LOAD
150 KG



REGULAR
USAGE

tb davies

TB Davies INSUL8-S

Fibreglass Professional Swingback Step

Our robust, Heavy-Duty Fibreglass step ladder series features a versatile tool tray and non-conductive stiles – perfect for electrical work. Built with sturdy C-section fibreglass stiles reinforced with aluminium treads, the GRP step ladders offer a durable, lightweight solution for the active professional.

- Non-conductive fibreglass stiles to 30,000 volts (EN61478), ideal for working around electricity
- Integrated multi-function tool tray
- Reinforced 320 x 248mm checker-plate platform (platform steps only)
- Comfortable 80mm treads
- Hinged metal locking stays, provide optimal stability
- Box section back legs with heavy-duty bracing
- Large feet angled to maximise ground contact and reduce slip
- EN131 Professional



Multi-purpose tool tray fitted


TB DAVIES INSUL8-S FIBREGLASS PROFESSIONAL SWINGBACK STEP

SKU	TREAD COUNT*	MAX STEP HEIGHT (M)	APPROX. WORKING HEIGHT†(M)	CLOSED HEIGHT (M)	WIDTH (M)	OPEN DEPTH (M)	WEIGHT (KG)
1235-004	4	0.26	2.01	1.14	0.45	0.83	5.7
1235-005	5	0.52	2.27	1.42	0.49	1.01	7.0
1235-006	6	0.78	2.53	1.70	0.52	1.19	8.0
1235-008	8	1.30	3.05	2.26	0.59	1.55	10.5
1235-010	10	1.83	3.58	2.82	0.66	1.91	13.1

Where applicable, Approx. Working Height[†], is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.

*Tread count includes top platform step.

†Heavy Item - 2-person lift required.



Scan For Video



NEXT DAY
DELIVERY



3-YEAR
WARRANTY



MAX LOAD
150 KG



REGULAR
USAGE

tb davies

TB Davies INSUL8-P

Fibreglass Professional Platform Step

Our robust, Heavy-Duty Fibreglass step ladder series features a versatile tool tray and non-conductive stiles – perfect for electrical work. Built with sturdy C-section fibreglass stiles reinforced with aluminium treads, the GRP step ladders offer a durable, lightweight solution for the active professional.

- Non-conductive fibreglass stiles to 30,000 volts (EN61478), ideal for working around electricity
- Integrated multi-function tool tray
- Reinforced 320 x 248mm checker-plate platform (platform steps only)
- Comfortable 80mm treads
- Hinged metal locking stays, provide optimal stability
- Box section back legs with heavy-duty bracing
- Large feet angled to maximise ground contact and reduce slip
- EN131 Professional



Quickly & smoothly fold the step ladder with the easy-pull handle

TB DAVIES INSUL8-P FIBREGLASS PROFESSIONAL PLATFORM STEP

SKU	TREAD COUNT*	PLATFORM HEIGHT (M)	APPROX. WORKING HEIGHT†(M)	CLOSED HEIGHT (M)	WIDTH (M)	OPEN DEPTH (M)	WEIGHT (KG)
1236-004	4	1.04	2.79	1.81	0.54	0.99	8.8
1236-005	5	1.30	3.05	2.09	0.57	1.17	10.2
1236-006	6	1.56	3.31	2.37	0.61	1.35	11.4
1236-008	8	2.09	3.84	2.93	0.67	1.72	14.0

Where applicable, Approx. Working Height[†], is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.

*Tread count includes top platform step.

†Heavy Item - 2-person lift required.



INSUL8-P

Bespoke Access Solutions

At TB Davies, we recognise the importance of sustainability in today's world. As part of our commitment to reduce our carbon footprint, we have adapted our processes to include more digital interaction. We conduct meetings via online platforms such as Zoom or Microsoft Teams for preliminary discussions and needs assessment. This approach allows us to understand your unique requirements and prepare tailored solutions in a more eco-friendly manner. Despite the digital preparation, we understand the significance of on-site confirmation. Our team is always ready to visit your premises when necessary, ensuring the accuracy of our plans and reassuring you of our commitment. Combining digital convenience with traditional on-site verification, we are delivering on our promise of providing bespoke solutions, all while keeping our planet in mind.





NEXT DAY
DELIVERY



10-YEAR
WARRANTY



MAX LOAD
150 KG



INTENSIVE
USAGE



DURACLIMB
STEP

TB Davies PROBAT

Aluminium Industrial Platform Step

Experience unparalleled stability with the Probat platform step ladder, designed for rigorous use in even the most challenging environments. Rigorously tested to support 360kg, it features 50mm aluminium scaffold tubing for both front and rear stiles. The massive 100mm deep treads employ 'Duraclimb' spun-rung technology, ensuring the most robust mechanical connection for heavy-duty applications.

- Manufactured from 50mm Aluminium scaffold tube for maximum rigidity and stability
- Featuring tough spun-rung 'Duraclimb' technology for intensive use
- Extra-strong 390 x 380mm bi-folding platform
- Mammoth 100mm deep steps for maximum climbing support
- Convex oversized feet ensure maximum ground contact and grip
- EN131 Professional




100mm deep treads




Super-sized rubber, non-slip
feet



Work tray & hook



Unique folding platform



Extra-thick 50mm tube






Work tray & hook holds up to 10kg



Folds easily for transport & storage



High handrail



In folded, storage position

TB DAVIES PROBAT ALUMINIUM INDUSTRIAL PLATFORM STEP							
SKU	TREAD COUNT*	PLATFORM HEIGHT (M)	APPROX. WORKING HEIGHT†(M)	CLOSED HEIGHT (M)	WIDTH (M)	OPEN DEPTH (M)	WEIGHT (KG)
1205-004	4	0.95	2.70	1.91	0.69	0.98	10.8
1205-005	5	1.20	2.95	2.16	0.72	1.14	12.4
1205-006	6	1.42	3.17	2.41	0.75	1.30	14.5
1205-008	8	1.90	3.65	2.91	0.81	1.62	17.0
1205-010	10	2.37	4.12	3.41	0.87	1.94	21.5

Where applicable, Approx. Working Height[†], is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.

*Tread count includes top platform step.

†Heavy Item - 2-person lift required.



DURA CLIMB

Utilising robust spun-rung "Duraclimb" technology, treads are firmly secured, offering the most resilient mechanical connection for demanding applications.



NEXT DAY
DELIVERY



5-YEAR
WARRANTY



MAX LOAD
150 KG



INTENSIVE
USAGE

tb davies

TB Davies HDUTY-P Aluminium Professional Platform Step

Enhanced to meet the new EN131 Professional ladder standard, these versatile industrial steps come in both platform and swing-back styles. Wider than their classic Class 1 counterparts, they are manufactured from heavy-duty channel and box section stiles and riveted treads for lasting durability.

Available in sizes 4, 5, 6, 8, 10 treads*.

*3 & 12 treads are available as a Platform Step only.

- Large 330 x 255 checker-plate platform (platform steps only)
- Comfortable 80mm treads
- Heavy duty all aluminium construction
- Hinged metal locking stays provide optimal stability
- Box section back legs with heavy-duty bracing
- Slip resistant feet provide a firm footing
- EN131 Professional



All-metal hinge mechanism on the revised Platform Step Ladder



Duraclimb tread provides maximum strength connection

TB DAVIES HDUTY-P ALUMINIUM PROFESSIONAL PLATFORM STEP							
SKU	TREAD COUNT*	PLATFORM HEIGHT (M)	APPROX. WORKING HEIGHT†(M)	CLOSED HEIGHT (M)	WIDTH (M)	OPEN DEPTH (M)	WEIGHT (KG)
1202-023	3	0.65	2.40	1.34	0.44	0.65	4.5
1202-024	4	0.89	2.64	1.57	0.47	0.81	5.2
1202-025	5	1.12	2.87	1.81	0.50	0.97	6.8
1202-026	6	1.36	3.11	2.06	0.53	1.13	7.5
1202-028	8	1.83	3.58	2.55	0.59	1.48	9.5
1202-030	10	2.28	4.03	3.04	0.65	1.84	12.0
1202-031	11	2.52	4.27	3.28	0.68	1.99	13.2
1202-032	12	2.76	4.51	3.53	0.71	2.15	14.2

Where applicable, Approx. Working Height†, is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.

*Tread count includes top platform step.

†Heavy Item - 2-person lift required.



Platform

NEXT DAY
DELIVERY5-YEAR
WARRANTYMAX LOAD
150 KGREGULAR
USAGE


tb davies

TB Davies MAXI

Aluminium Professional Platform Step

The Maxi platform step ladder, ideal for frequent use, boasts a spacious cast aluminium safety platform set at a comfortable 75-degree angle. Its generous 110mm deep treads utilize 'Duraclimb' spun-rung technology, ensuring a highly robust mechanical connection for everyday applications.

- Featuring tough spun-rung 'Duraclimb' technology for intensive use
- Comfortable 75 degree safe-climbing angle
- Large 110mm deep steps for fatigue-free standing
- High strength nylon components reduce wear and tear
- Spacious storage tray for material and tools
- EN131 Professional



Improved top platform tread



New & improved fitted tool tray

TB DAVIES MAXI ALUMINIUM PROFESSIONAL PLATFORM STEP

SKU	TREAD COUNT*	PLATFORM HEIGHT (M)	APPROX. WORKING HEIGHT†(M)	CLOSED HEIGHT (M)	WIDTH (M)	OPEN DEPTH (M)	WEIGHT (KG)
1211-023	3	0.65	2.40	1.38	0.44	0.70	4.2
1211-024	4	0.88	2.63	1.62	0.47	0.86	5.2
1211-025	5	1.12	2.87	1.88	0.50	1.02	6.2
1211-026	6	1.36	3.11	2.12	0.53	1.18	7.2
1211-027	7	1.59	3.34	2.37	0.56	1.34	8.2
1211-028	8	1.82	3.57	2.62	0.59	1.50	9.2

Where applicable, Approx. Working Height†, is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.

*Tread count includes top platform step.

†Heavy Item -2-person lift required.





NEXT DAY
DELIVERY



3-YEAR
WARRANTY



MAX LOAD
150 KG



INTENSIVE
USAGE

tb davies

TB Davies PREMIER-XL Aluminium Trade Platform Step

This lightweight stepladder has twin handrails fitted for an easy climb, with an integrated multi-function tool tray. Now available under EN131 Professional, making this a perfect step for all offices, retail, education and similar environments.


- Twin safety handrails to assist with climbing - supplied flat-pack, some assembly required before first
- Extra-large 120mm anti-slip treads with edge protection
- Comfortable 270 x 250mm platform
- EN131 Professional



Oversized handles to help increase reassurance when climbing the step



Handrails are supplied flat-pack, for easy assembly on delivery



Large top standing platform, ideal for a wide range of jobs

TB DAVIES PREMIER-XL ALUMINIUM TRADE PLATFORM STEP

SKU	TREAD COUNT*	PLATFORM HEIGHT (M)	APPROX. WORKING HEIGHT†(M)	CLOSED HEIGHT (M)	WIDTH (M)	OPEN DEPTH (M)	WEIGHT (KG)
1203-003	3	0.62	2.37	1.37	0.41	0.66	4.0
1203-004	4	0.84	2.59	1.59	0.44	0.82	4.6
1203-005	5	1.05	2.80	1.81	0.46	0.97	5.4
1203-006	6	1.27	3.02	2.04	0.49	1.12	6.4
1203-007	7	1.49	3.24	2.27	0.51	1.28	7.4
1203-008	8	1.71	3.46	2.49	0.53	1.42	8.8

Where applicable, Approx. Working Height†, is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.

*Tread count includes top platform step.

†Heavy Item - 2-person lift required.



NEXT DAY
DELIVERY3-YEAR
WARRANTYMAX LOAD
150 KGREGULAR
USAGE

tb davies

TB Davies HORIZON

Aluminium Trade Platform Step

Now rated EN131 Professional, this ladder is perfect for workplace use. Its slim design and extra-high continuous handrail provide exceptional ease and comfort, ensuring a seamless experience during operation.

- High continuous handrail for ease of use
- Deep comfortable treads
- Strong sturdy 264 x 258mm platform
- EN131 Professional

TB DAVIES HORIZON ALUMINIUM TRADE PLATFORM STEP

SKU	TREAD COUNT*	PLATFORM HEIGHT (M)	APPROX. WORKING HEIGHT†(M)	CLOSED HEIGHT (M)	WIDTH (M)	OPEN DEPTH (M)	WEIGHT (KG)
1212-003	3	0.62	2.37	1.33	0.44	0.69	3.6
1212-004	4	0.84	2.59	1.57	0.46	0.84	4.2
1212-005	5	1.06	2.81	1.81	0.49	1.00	4.8
1212-006	6	1.28	3.03	2.04	0.51	1.19	5.4
1212-007	7	1.51	3.26	2.28	0.53	1.30	6.4
1212-008	8	1.73	3.48	2.53	0.56	1.50	8.0

Where applicable, Approx. Working Height†, is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.

*Tread count includes top platform step.

†Heavy Item - 2-person lift required.



NEED ADVICE?

If you have any questions about our range of products or suitability for a specific requirement, please contact us on 029 2132 0000 or email sales@tbdavies.co.uk

