



Bowers & Wilkins

705 S3 Signature

Technical Information



Technical Features	Decoupled Carbon Dome tweeter Solid Body Tweeter-on-Top Continuum™ cone bass / midrange Flowport™
Description	2-way vented-box system
Drive Units	1x ø25mm (1 in) Decoupled Carbon Dome high-frequency 1x ø165mm (6.5 in) Continuum cone bass / midrange
Frequency Range	-6dB 45Hz - 33kHz
Frequency Response (+/-3dB from reference axis)	50Hz - 28kHz ±3dB
Sensitivity (on axis at 2.83Vrms at 1m)	88dB
Harmonic Distortion	2nd and 3rd harmonics (90dB, 1m on axis) <1% 100Hz - 22kHz <0.5% 150Hz - 20kHz
Nominal Impedance	8Ω (minimum 3.7Ω)
Recommended Amplifier Power	30W–120W into 8Ω on unclipped programme
Max. Recommended Cable Impedance	0.1Ω
Dimensions	Height: 345 mm (13.6 in) cabinet only 413 mm (16.3 in) including tweeter Width: 192 mm (7.6 in) cabinet only Depth: 297 mm (11.7 in) cabinet only 337 mm (13.3 in) including grille and terminals
Net Weight	10.85 kg (23.9 lbs)
Finishes	Cabinet: Datuk Gloss Midnight Blue Metallic Grille: Black