



INSTALLATION

DRIVER BACKREST 8990

PARTS INCLUDED

- 1 Driver Back Rest Assembly
- 1 Right Side Mounting Bracket
- 1 Left Side Mounting Bracket
- 4 M8 x 1.25 x 80mm Socket Head Cap Screws
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

TOOLS SUGGESTED

Set of Standard Hex Wrenches, Set of Metric Hex Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

NOTE: THE POUCH ON THE BACK REST IS NOT REMOVABLE. IT IS PERMANENTLY ATTACHED WITH PLASTIC BUTTON FASTENERS.

STEP 2 Remove the passenger handles from the motorcycle. Using the M8 X 1.25 X 80mm Socket Head Cap Screws, install the mounting brackets as shown in PIC.1.

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.



CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
 - The product must be properly installed, maintained and operated under normal conditions.
 - Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
 - Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Kuryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

For purchasing Kuryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Kuryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.


©2005 Kuryakyn USA® All Rights reserved.



STEP 3

PIC.2 shows the Driver Back Rest adjustment hub in the unlocked position. PIC.3. shows the adjustment hub in the locked position (Red Arrow to Red Padlock). Be sure **both** adjustment hubs are in the **unlocked** position for the next step.


PIC 2



STEP 4

Choose one of the three mounting positions on the mounting brackets. If you are unsure which position will be most comfortable for you then choose the mounting notch in the middle. To attach the Driver Back Rest hold it an upright position and drop the adjustment hubs below the front of the drivers seat. Move the adjustment hubs back toward the mounting brackets being careful not to tear the seat. You must slightly "spring" the arms outward to reach the Left and Right Side Mounting Brackets.

PIC 3



STEP 5

Lock the Driver Back Rest in position by rotating the knob on the outside of the right adjustment hub counter clock-wise. Lock the left side by rotating the knob on the left side adjustment hub clock-wise.

STEP 6

You can adjust the backrest for maximum comfort by unlocking the adjustment hubs, "springing" the arms outward and moving them to the desired position on the Left and Right Side Mounting Brackets.

CAUTION!

Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

ATTENTION!

It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

PIC 4

