

Haknuckyklar till olika låsmuttrar

Gänga	Låsmutter DIN 1804 (Spårmutter)				Låsmutter DIN 1816 (Hålmutter)			
	d_2	b	t	Antal spår	d_2	d_4	t	Antal hål
M 6×0.75	16	4	1.5	4	16	2.5	4	4
M 8×1	20	4	1.5	4	20	2.5	4.5	4
M 10×1	25	5	2	4	25	3	4.5	4
M 12×1.5	28	5	2	4	28	3	5	4
M 14×1.5	30	5	2	4	30	4	5	4
M 16×1.5	32	5	2	4	32	4	6	4
M 18×1.5	34	6	2.5	4	34	4	6	4
M 20×1.5	36	6	2.5	4	36	4	6	4
M 22×1.5	40	6	2.5	4	40	4	6	4
M 24×1.5	42	6	2.5	4	42	4	6	4
M 26×1.5	45	7	3	4	45	5	6	4
M 28×1.5	50	7	3	4	50	5	7	4
M 30×1.5	50	7	3	4	50	5	7	4
M 35×1.5	55	7	3	4	55	5	7	4
M 38×1.5	58	8	3.5	4	58	5	8	4
M 40×1.5	62	8	3.5	4	62	6	8	4
M 42×1.5	62	8	3.5	4	62	6	8	4
M 45×1.5	68	8	3.5	6	68	6	8	6
M 48×1.5	75	8	3.5	6	75	6	10	6
M 50×1.5	75	8	3.5	6	75	6	10	6
M 55×1.5	80	10	4	6	80	6	10	6
M 60×1.5	90	10	4	6	90	6	10	6
M 65×1.5	95	10	4	6	95	8	12	6
M 70×1.5	100	10	4	6	100	8	12	6
M 75×1.5	110	10	4	6	110	8	12	6
M 80×2	115	10	4	6	115	10	12	6
M 85×2	120	10	4	6	120	10	12	6
M 90×2	130	10	4	6	130	10	12	6
M 95×2	135	12	5	6	135	10	12	6
M 100×2	145	12	5	6	145	10	12	6
M 105×2	155	12	5	6	155	10	12	6
M 110×2	155	12	5	6	155	10	12	6
M 115×2	165	12	5	6	165	10	15	6
M 120×2	165	12	5	6	165	10	15	6
M 125×2	180	12	5	8	180	10	15	8
M 130×3	180	12	5	8	180	10	15	8
M 140×3	195	12	5	8	195	10	15	8
M 150×3	205	12	5	8	205	10	15	8
M 160×3	220	12	5	8	220	10	15	8
M 170×3	230	16	7	8	230	10	15	8

(Låsmuttrar enl. SMS 487 har liknande utförande men avvikande mått.)