


Fästkonor för borrhuckar

(anslutningsmått) enligt svensk standard SS 710 och DIN 238



| Konans beteckning | D | d | L | L ₁ | a min. | f | c ¹⁾ | Konicitet | $\frac{\alpha}{2}$ | Borrhuckens maximala spänn diam. 2) |
|-------------------|--------|--------|------|----------------|--------|-----|-----------------|---------------------------|--------------------|-------------------------------------|
| B 6 | 6,350 | 5,850 | 10 | 13 | 3 | 0,5 | 1 | 1:20 | 1°25'56" | 3 |
| B 10 | 10,095 | 9,371 | 14,5 | 18 | 3,5 | 1 | 1,5 | 1:20,047 (Morsekona 1) | 1°25'43" | 6 |
| B 12 | 12,065 | 11,142 | 18,5 | 22 | 3,5 | 1 | 1,5 | | | 10 |
| B 16 | 15,732 | 14,533 | 24 | 28 | 4 | 1,5 | 1,5 | 1:20,020 (Morsekona 2) | 1°25'51" | 13 |
| B 18 | 17,780 | 16,182 | 32 | 36 | 4 | 1,5 | 1,5 | | | 16 |
| B 22 | 21,792 | 19,759 | 40,5 | 45 | 4,5 | 2 | 2 | 1:19,922 (Morsekona 3) | 1°26'16" | 20 |
| B 24 | 23,825 | 21,290 | 50,5 | 55 | 4,5 | 2 | 2 | | | 25 |