








Suitable screwdrivers for different screws



Machine screws









Slotted head

Driver thickness × driver width mm	For Metric screws M				For Unified screws UNC		
	MCS	MSCS	MFS	MKFS	ULCS	UFS	UKFS
							
0.4×2.5	M 1.6	M 1.6	M 1.6	M 1.6	–	–	–
0.5×3 (0.5×3.5)	M 2	M 2	M 2	M 2	–	–	–
0.6×3.5 (0.6×4)	M 2.5	M 2.5	M 2.5	M 2.5	–	–	–
0.8×4 (0.8×5.5)	M 3	M 3	M 3	M 3	No 5	No 5	No 5
1.0×5.5 (1.0×6.5)	M 3.5	M 3.5	M 3.5	M 3.5	No 6, 8	No 6, 8	No 6, 8
1.2×6.5	M 4	M 4	M 4	M 4	No 10, 12	No 10, 12	No 10, 12
1.2×8	M 5	M 5	M 5	M 5	–	–	–
1.6×10	M 6	M 6	M 6	M 6	¼	¼	¼
2.0×12 (2×13)	M 8	M 8	M 8	M 8	5/16, 3/8, ½	5/16, 3/8, ½	5/16, 3/8, ½
2.5×14 (2.5×16)	M 10	M 10	M 10	M 10	5/8, ¾	5/8, ¾	5/8, ¾

Screwdriver dimensions in brackets refers to older standards.



Cross head (Phillips and Pozidriv/Supadriv)

Cross head no	For Metric screws M			For Unified screws UNC		
	MRX	MFX	MFKX	URX	UFX	UKFX
						
0	M 1.6 M 2	M 1.6 M 2	M 1.6 M 2			
1	M 2.5 M 3	M 2.5 M 3	M 2.5 M 3			
2	M 3.5 M 4 M 5	M 3.5 M 4 M 5	M 3.5 M 4 M 5	No 5 No 6 No 8 No 10	No 5 No 6 No 8 No 10	No 5 No 6 No 8 MR 10
3	M 6	M 6	M 6	No 12 ¼	No 12 ¼	No 12 ¼
4	M 8 M 10	M 8 M 10	M 8 M 10	5/16 3/8 7/16 ½	5/16 3/8 7/16 ½	5/16 3/8 7/16 ½