

# TECHNICAL DATA SHEET



**Product code:** 5391 **Sector:** Automotive / Classic  
Commercial / Agricultural

**Issue No:** 3

**Issue Date:** 17/01/23

## UNIVERSAL BRAKE FLUID DOT 4

Brake & Clutch Fluid

### Application

Suitable for passenger car, light commercial (LCV) and heavy goods vehicles (HGV). Designed for high performance braking systems where a non-mineral fluid is required and high braking temperatures are experienced.

### Performance Profile

U.S. FMVSS No.116 DOT 4, DOT 3  
SAE J 1704, SAE J 1703  
ISO 4925 (Class 4 & 3)

### Typical Characteristics

Equilibrium Reflux Boiling Point	≥260°C
Wet Equilibrium Boiling Point	≥165°C
Kinematic Viscosity @-40°C, cSt	1340
Kinematic Viscosity @100°C, cSt	2.41
Density @ 20°C, g/ml	1.05

### Features & Benefits

- Enhanced performance against water absorption, which improves resistance to vapour lock.
- Compatible with DOT 3, 'standard' DOT 4 & DOT 5.1 brake fluid.

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website [www.millersoils.co.uk](http://www.millersoils.co.uk)

**Footnotes:** Warning: Not to be used in mineral oil systems. Always refer to manufacturer handbook prior to use.



**MADE IN BRITAIN**

**Millers Oils Ltd**  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)