

INSTALLATION INSTRUCTIONS

DRAG SPECIALTIES FENDER SKINS

ATTENTION INSTALLER (if other than owner): Please forward this instruction sheet to the purchaser of this product. These instructions contain valuable information necessary to the end user.

INTRODUCTION: These instructions describe the procedure for properly installing Drag Specialties Fender Skins. Review instructions carefully before beginning, as they contain important information. Please retain for future reference.

The following notations distinguish particularly important information in the instructions.

NOTE: A NOTE provides key information to make procedures easier or clearer.

CAUTION: A CAUTION indicates special procedures that must be followed to avoid damage to the motorcycle and/or accessories.

WARNING!: A **WARNING** indicates special procedures that must be followed to avoid injury to a motorcycle operator or person inspecting or repairing the motorcycle.

Locate your year and model and proceed with the installation instructions.

Dyna Glide 06-UP (all models)

FL 97-UP (all models)

Softail, FLSTF 07-UP (all models). Will fit Deluxe if fender rack is removed.

Sportster 04-UP (all models except the 48).

NOTE: These Fender Skins are a direct fit and no modifications will be needed.

1. Remove your seat.
2. Install the Fender Skin using the Black zinc screw and washer provided.
3. Reinstall your solo seat using your original mounting hardware.

FXR (all models)

Dyna Glide 91-05 (all models)

Sportster 57-03 (all models)

Softail 84-UP, FLST 84-06

FX, FXWG, FL, FLH 58-84 (all models)

NOTE: Follow instructions carefully to insure a good fit. Provided in your kit:

- A. 5/16" punch
- B. 1/4" Black zinc washer
- C. 1/4" Black zinc button head screw
- D. 1" x 1" Hook fastener

READ BEFORE INSTALLATION BEGINS.

CAUTION 1: Your particular kit may have two 1/4" button head screws: one course thread and one fine thread. Typically, 1995 and earlier H-D models use a fine thread screw and 1996 and later models use a course thread screw. **ALWAYS DOUBLE CHECK YOUR THREAD PITCH CAREFULLY; HAND START ALL SCREWS.**



CAUTION 2: If it becomes necessary to shorten the length of your Fender Skin, always seal the threads with hot melt glue or contact adhesive. Allow to dry prior to trimming.

IF YOUR FRONT SOLO MOUNTS WITH SIDE MOUNT, START HERE:

1. Remove your front solo seat.
2. Mount your Fender Skin using the recommended screw and washer. **See CAUTION 1 above.**
3. Pull Fender Skin slightly forward, center and locate where the fastening loop makes contact with fender. Using a wax and grease remover, clean fender and apply pressure-sensitive hook material. Secure Fender Skin and reinstall your solo seat.

IF YOUR SOLO SEAT HAD A REAR MOUNT AND BOLTS THROUGH THE FENDER, START HERE:

1. Remove your front solo seat.
2. Mount your Fender Skin using the recommended screw and washer. **See CAUTION 1 above.**
3. Pull the Fender Skin slightly forward and center left to right. Maintaining slight tension, mark the location of the hole in the fender with chalk. Measure the Fender Skin to make sure the hole is centered correctly. Remove the Fender Skin.
4. Now that the hole is located on the Fender Skin, place a piece of wood or rigid plastic behind the hole, place punch over marked area, and while holding the punch with a pliers, strike with a hammer to remove hole. Before punching a second hole (if needed) clean material from punch.
5. Reinstall the Fender Skin and solo seat.

