



Harley-Davidson® Softail 1984-99

Mounting Suggestions

Harley-Davidson® Softail 1984-99

One-Piece Seat

Mounting Suggestions

Harley-Davidson® Softail 1984-99

Two-Piece Seat

Mounting Suggestions

Harley-Davidson® Softail 1984-99

Solo Seat

Mounting Suggestions

Harley-Davidson® Softail 1984-99

Passenger Seat



Mounting Suggestions Harley-Davidson® Softail 1984-99 One-Piece Seat



Baseplate Features:

Seats are built on 16 gauge formed steel baseplates. The baseplates have rubber supports at contact points. Rear seat features carpet to protect the fender.

NOTE: Mustang Softail seats will fit all Softail models except 1999-earlier FLSTS Heritage Springers.

Removal of Stock Seat

1. Remove one side mounting bolt on each side of driver's seat.
2. Remove rear fender screw.
3. Remove seat from bike by sliding it back and up.

Mounting of Mustang Solo Seat

1. Clip welded nose tab into frame mount behind gas tank.
2. Secure rear of seat with rear fender screw.



These steps are guidelines to help you install your new Mustang Product. If you need further assistance, please call us at 800-243-1392 or 860-582-9633, Monday through Friday 9:00 – 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "[Support](#)".

Refers to part numbers 75596, 76372, 75157, 75629, 75444, 75110, 75112, 75631, 75303, 75503, 75735, 75502

[back](#)



Mounting Suggestions Harley-Davidson® Softail 1984-99 Two-Piece Seat



Baseplate Features:

Seats are built on 16 gauge formed steel baseplates. The baseplates have rubber supports at contact points. Rear seat features carpet to protect the fender.

NOTE: Mustang Softail seats will fit all Softail models except 1999-earlier FLSTS Heritage Springers.

Removal of Stock Seat

1. Remove the side mounting bolt on each side of driver's seat.
2. Remove rear fender screw.
3. Remove seat from bike by sliding it up and back.

Mounting of Mustang Seat

1. Remove two 1/4-20 screws in the rear of the Mustang solo baseplate.
2. Align passenger seat front chrome tabs with threaded holes in back of solo baseplate.
3. Secure passenger seat and solo together with screws from step 1. Seat becomes a one-piece unit.
4. Clip welded nose tab of solo into the frame mount behind the gas tank and secure passenger seat tab with stock screw in rear fender.
5. Align the solo side brackets and attach with large Allen screws. **NOTE:** The solo side brackets can be removed (and not used) when mounting the solo and passenger seat combination.

NOTE: Nylon washer should be under the rear bracket only on '95 and earlier models.
Mustang passenger seat can only be mounted to a Mustang solo seat.

These steps are guidelines to help you install your new Mustang Product. If you need further assistance, please call us at 800-243-1392 or 860-582-9633, Monday through Friday 9:00 – 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under [“Support”](#).

Refers to part numbers 75122, 75123, 75141, 75142, 75490, 75492, 75506, 75509, 75512, 75513, 75514, 75750, 75751, 75757, 75764, 79104, 79114, 79124, 79134, 79228, 79229, 79248, 79249

[back](#)



Mounting Suggestions Harley-Davidson® Softail 1984-99 Solo Seat



Baseplate Features:

Seats are built on 16 gauge formed steel baseplates. The baseplates have rubber supports at contact points. Rear seat features carpet to protect the fender.

NOTE: Mustang Softail seats will fit all Softail models except 1999-earlier FLSTS Heritage Springers.

Removal of Stock Seat

1. Remove two side mount bolts, one on each side of driver's seat.
2. Remove rear fender screw.
3. Remove seat from bike by sliding it back and up.

Mounting of Mustang Solo Seat

1. Clip nose tab into frame mount behind gas tank.
2. Align side brackets with threaded holes in frame.
3. Install and tighten two 1/2-13 side mount bolts.

*Enjoy the comfort of your
new Mustang seat!*



These steps are guidelines to help you install your new Mustang Product. If you need further assistance, please call us at 800-243-1392 or 860-582-9633, Monday through Friday 9:00 – 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under [“Support”](#).

Refers to part numbers 75512, 75490, 75750, 79124, 75757, 79104, 75506, 79248, 79228, 75141, 75122

[back](#)



Mounting Suggestions Harley-Davidson® Softail 1984-99 Passenger Seat



Baseplate Features:

Seats are built on 16 gauge formed steel baseplates. The baseplates have rubber supports at contact points. Rear seat features carpet to protect the fender.

NOTE: Mustang Softail seats will fit all Softail models except 1999-earlier FLSTS Heritage Springers.

Mounting of Mustang Passenger Seat

1. Remove Mustang solo seat from bike.
2. Remove two 1/4-20 screws located at back of Mustang solo seat baseplate.
3. Align passenger seat front chrome tabs with threaded holes in back of solo baseplate.
4. Secure rear seat and solo together with screws from step 2. Seat becomes a 1-piece unit.
5. Align chrome rear tab with threaded fender hole and secure with stock screw.
6. Install and tighten side mount bolts.

NOTE: Mustang passenger seat can only be mounted to a Mustang solo seat.



These steps are guidelines to help you install your new Mustang Product. If you need further assistance, please call us at 800-243-1392 or 860-582-9633, Monday through Friday 9:00 – 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under [“Support”](#).

Refers to part numbers 75513, 75514, 75492, 75751, 75513, 79134, 79114, 75764, 75509, 79249, 75142, 79229, 75123

[back](#)