



MOUNTING SUGGESTIONS:

Yamaha Bolt 2013-2017 Passenger Seat

Hardware: Rear mounting bracket
T-bracket with 1/4"-20 stud
Small shoulder washer
1/4"-20 flange nut

Tools needed: 7/16" hex wrench
4mm Allen wrench

Installation of Mustang Seat:

Note: If you are using both a solo and a passenger seat, the passenger seat must be installed before the solo. The Mustang passenger seat does not work with the stock solo.



1. Remove the four Allen bolts from the fender with a 4mm Allen wrench.



2. Attach the supplied T-bracket securely to the frontmost fender holes using the stock bolts. The 1/4"-20 threaded stud must be positioned toward the front of the motorcycle. Place the supplied shoulder washer over the stud.

3. Attach the supplied rear mounting bracket securely to the rearmost fender holes using the stock bolts.



4. Slide the Mustang passenger seat back on the fender, engaging the rear mounting bracket to the rear fender bracket, and lower the seat onto the T-bracket.

5. Secure passenger to the T-bracket with the supplied 1/4"-20 flange nut using a 7/16" wrench.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75692, 75694, 79831, 79833

You are cordially invited to
— Tour the Mustang Factory —

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.