



Nozzle kit SPRAYFlxx alkali

Item number: 80 690
EAN: 4103810806902
Discount group: A

Technical data

Temperature range (°C): +5 /+30
 Operating pressure max. (bar): 2,5
 Adjusting and swivelling nozzle VA
 Spray pattern: punctual jet = full jet + cone jet = spray jet
 Spraying quantity with full jet (ml/min): 618
 Spraying quantity with spray jet (ml/min): 348
 Spraying distance with full jet (m): 5,1
 Spraying distance with spray jet (m): 1,4

Materials

Adjusting and swivelling nozzle: stainless steel
 Seal: FKM (Viton®)
 Nozzle body: ABS
 Union nut: PA
 Dimensions øxL (mm): 23 x 52
 Weight (kg): 0,0103

Adjusting nozzle with plastic adjusting nut ABS

Spray pattern: punctual jet = full jet + cone jet = spray jet
 Spraying quantity with full jet (ml/min): 480
 Spraying quantity with spray jet (ml/min): 192
 Spraying distance with full jet (m): 4,6
 Spraying distance with spray jet (m): 0,8

Materials

Adjusting nozzle with plastic adjusting nut: PA
 Extension tube: PA
 Union nut: PA
 Dimensions øxL (mm): 23 x 91
 Weight (kg): 0,0110

Foam nozzle

Spray pattern: Foam
 Spraying quantity (ml/min): 288
 Spraying distance (m): 0,8

Materials

Foam nozzle: Stainless steel + PP
 Nozzle body: stainless steel
 Foam nozzle insert: PA
 Dimensions øxL (mm): 17 x 28
 Weight (kg): 0,0096

Specification

- Adjusting and swivelling nozzle stainless steel (80 681)
- Viton® FKM seal
- Ball joint with union nut
- Extension tube with union nut
- Foam nozzle
- Nozzle insert

Special notes

- Suited for alkaline media
- Swivels to a maximum angle of 60° by means of ball joint
- Universally adjustable spray pattern by means of adjustable nozzle
- Wear-resistant

- UV-resistant

Packaging

Dimensions LxWxH (mm):	140 x 80 x 25
Weight including package (kg):	0,0316
Packing unit:	1.0