

VARIO® SOLO Overvoltage Protection Plug

With acoustic signal and replaceable fuse

- ✓ Dual function reliability due to operating display and acoustic alarms
- ✓ With integrated fuse drawer for holding a fuse and spare fuse

Audible Alarm

After a protective circuit for overvoltage protection (thermal fuse, micro fuse), an acoustic signal sounds. The connected device continues to operate.

Replaceable Fuse

After the overvoltage protection is triggered, the protection devices can be restored. The defective fuse can be easily removed and replaced with the included replacement fuse.

Operating Display

The red LED indicates if the overvoltage protection is properly guaranteed.

Technical Data

- SPD based on 61643-11 Typ 3
- $U_n = 230V \sim 16 A 50 Hz$
- L-N: $U_{oc} = 5000 V / U_p = < 1,0 kV$
- L/N-PE: $U_{oc} = 5000 V / U_p = < 1,5 kV$
- $U_c = 255V \sim 50 Hz$
- $I_{max} (8/20): 6,5 kA$

Dimensions: 75 x 65 x 49 (with plug 85) mm

EAN: 4012096000587

Packing unit: 5

Article no.: 0460x0500



VARIO®
SOLO

Subject to technical changes.
Special designs on request.

Review Date: 04/2013