

971 MODULAR ENTRANCE PANELS

IACCESS READER MODULE FOR USOA



Code : **9710025**

Model : **MLP-000**

Description

Complete module for USOA entrance panel. iACCESS reader. 1 window. It includes an ELP-000 electronic module and CLP-000 front glass

iACCESS SYSTEM

iACCESS is an Access Control System based in Proximity RF Readers that are integrated in our 2 wire Door Phone entrance panels. Thus the system grants access to the users by means of electronic keys avoiding standard metal ones or even code memorizing.

Different key holders can access different locations of the facility, depending on the given total or partial access. iACCESS can encode keys that let access only temporally for instance during summer season (pool cleaners, lifeguards) or only during some specific hours (gardeners only during the morning). The system lets you form all these options like creating new keys for new users, cancelling lost ones and many other options very quick and easy using our website based application at <https://alcad-iaccess.com/>.

iACCESS offers convenience to the users as well as security and control on the people that access the facility for maintenance, etc... many common areas like: Roof, Terrace, Pool, etc..

9770095 ELP-000 Description

Electronic module for USOA entrance panel. Category: Spare parts. It incorporates an iACCESS reader to the entrance panel.

9770110 CLP-000 Description

Frontal glass for USOA entrance panel. Category: Spare parts. Front belonging to the complete module MLP-000

USOA is the Alcad entrance panel with a continuous profile and modular composition. It consists of frames of different sizes and with different numbers of windows where the different modules are fitted: as main audio or video module, push-button modules, iaccess module, card holders ... etc. There are two module sizes: P and G. The G modules occupy 2 frame windows, and the P modules occupy a single window.

Its modularity allows total freedom of choice for the creation of compositions and, at the same time, facilitates the integration of all technologies in the same equipment and with the same aesthetics.

Code		9710025
Model		MLP-000
Conection		Flat connector
Number of windows		1
Front • Materials • Color • Thickness	mm	• Tempered glass • White • 3mm
RFID Reader		Mifare Classic type A
Working temperature	°C	-10°C „, +55°C
Packing weight	Kg	0.11
Packing dimensions	mm	112 x 61 x 32 mm