



NAUSB-W-B

Reversible USB 2.0 gender changer (type A and B), black D-housing

Due to the rising digitisation the interface problems between audio/video networks, IT equipment, MP3 camcorders, etc. increase. A rugged solution is needed.

Neutrik's reversible USB gender changer, mounted in the standardized D-shape housing, and the rugged patch cables solve this problem.

Features & Benefits

- Ideal for audio networking and integration of computerbased equipment into audio systems
- Optional screen to chassis grounding
- Reversible insert offering type A or B on front or rear end
- IP65 ingress protection in mated condition with NKUSB-* and SCDP-* sealing gasket
- USB 2.0 gender changer type A-B (B-A)
- Universally accepted standard D-shape housing

Technical Information

| Product | |
|-----------------|-----------|
| Title | NAUSB-W-B |
| Connection Type | Adapter |
| Gender | female |

| Mechanical | |
|--------------------|----------------------|
| Wiresize | |
| Mounting direction | Front mounting |
| Chassis shape | D |
| Lifetime | > 1000 mating cycles |

| Material | |
|-----------------|-------------------------|
| Contact plating | Au |
| Contacts | Bronze (CuSn) |
| Insert | PVC |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell plating | Black chromium |

| Environmental | |
|---------------------|------------------------|
| Flammability | UL 94 V-0 |
| Standard compliance | USB 2.0 specifications |
| Temperature range | -25 °C to +85 °C |