

USB-C flush-mounted charger T65.00 Professional with Power Delivery (PD)

Item-no.: 6560x0001



USB-C flush-mounted insert with cover (white, 55x55mm) for installation into standard flush-mounted boxes \emptyset 65mm with device screws (!), installation according to DIN 49073

Compatible with 55x55 switch range programmes (inner dimensions of frame 55x55mm) white, similar to RAL9010 (e.g. Busch Balance SI by Busch-Jaeger or Standard 55 by GIRA, etc.)

65-Watt power supply with power delivery (PD) fast charging, for fast and safe charging of laptops, tablets, smartphones, wearables and further small electronic devices with USB-C port

Variable power adjustment: up to 65W

Supports different charging protocols e.g. Apple, Samsung, Quick Charge Version 4.0+, PD 3.0, etc.

Screw terminal to connect wires of the house installation, up to 2,5mm² max. (2xL/2xN – for easy looping in multiframes)

EHMANN advantage - 100% quality control, 5 years warranty

EHMANN quality – High-grade manufacturing and reliable function









USB-C flush-mounted charger T65.00 Professional with Power Delivery (PD)

Technical data

Power: max. 65 W 1x USB-C Output


110 - 230V / 50-60 Hz Input Voltage 5 - 20V Output voltage





Supported protocols:

FCP 5V, 9V, 12V SCP 3,6 - 5,5V, 25W AFC 5V, 9V, 12V QC3+ 5V, 9V, 12V, 3,6 - 12V PD3.0 65W, PPS, QC5 QC4 / QC4+ / BC 1.2 Apple Samsung



Connection: screw terminals up to 2,5 mm² (rigid)

Power consumption/Stand-by: < 0,08W

Short circuit/overload protection: electronic

In order to guarantee maximum charging power, please pay attention to using original / PD charging cables.









Before installing and using the device, please read the instruction manual carefully.

Item-no. 6560x0001

EAN 4012096011903

PU 10 Weight: net 120g

82 x 82 x 37 mm Dimension (L x W x H)