

UV-IPC-B125-APF28

Uniarch



Features

- Uniarch
- Bullet IP camera
- 1/3" Progressive Scan CMOS
- 5 Megapixel (2592x1944)
- 2.8 mm Lens
- 0 Lux
- IR Range 30 m
- Compression Ultra265/H.265/H.264
- RJ-45 10/100 Base TX
- PoE IEEE802.3af
- Weatherproof IP67
- IR Cut
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Uniview
Range	Uniarch
Image sensor	1/3", progressive scan, CMOS
Maximum resolution	5 Megapixel (2592x1944)
Main Stream rate	5 Mpx (1 ~ 20 FPS)
Extra Stream rate	720p (1 ~ 30 FPS)
Compression	Ultra265/H.265/H.264
Lens	2.8 mm
Minimum illumination	0.02 Lux (Colour), 0 Lux with IR
Infrared range	30 m
Image improvements	DWDR, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask, Smart IR
Day / Night	Automatic ICR filter
Internal memory	Does not have
Alarms	Does not have
Network interface	Ethernet 10/100 Base-TX Ethernet
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Interoperability	ONVIF
Power	DC 12 V / 4.5 W, PoE
Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP67
Dimensions	144 (H) x 60 (W) x 65 (D) mm
Weight	190 g