

LogiLink_®

Universal Travel Adapter 20 W PD

2x USB-A, 1x USB-C, 1x AC Outlet

Art. No.: PA0356











Included





Universally Compatible with 200+ Countries

Designed with 4 interchangeable plugs that can be adapted to outlets in several countries, including plugs in the EU, UK, USA and Australia, covering more than 200 countries and regions.



International outlet adapter accepts 10 types of plugs, use it both domestically and abroad.











Туре А

Туре В

Туре С

Туре Е

Type F







Type J







Type L

Type N



Versatile Charging

Supports 2x USB-A QC 3.0, 1x USB-C PD 3.0 and an AC outlet, perfect for powering multiple devices simultaneously.

GaN Technology

Compact design with advanced GaN technology for efficient, high-power performance and better heat management.





^{*}Adapter (AC-AC) does not convert voltage.

^{*}All trade names referenced are the registered trademarks of their respective owners.







^{*}Do not use with appliances requiring ground wire.

^{*}The specifications and pictures are subject to change without prior notice.

20 W PD Fast Charging

Built-in PD 20 W output, allowing you to quickly charge USB devices.





Enhanced Safety

Made of fire-resistant material with built-in 10 A fuse, safety shutters, and multiple charging protections for reliable use.



Portable Design

Lightweight and space-saving, perfect for travel.

Wide Applications

Great for travelers, remote workers, and students. Powers smartphones, tablets, laptops, and small appliances with ease.





^{*}Adapter (AC-AC) does not convert voltage.

^{*}The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.





^{*}Do not use with appliances requiring ground wire.

Specification:

Input	100–250 V AC 50/60 Hz 10 A, 2500 W max.
Output Interface	1x USB-C female, 2x USB-A female, 1x AC outlet
USB Output	USB-C: 5 V/3 A (15 W), 9 V/2.22 A (20 W), 12 V/1.67 A (20 W max.) USB-A1/A2: 5 V/3 A (15 W), 9 V/2 A (18 W), 12 V/1.5 A (18 W max.) USB-A1+USB-C, USB-A2+USB-C, USB-A1+USB-A2, USB-A1+USB-A2+USB-C: 5 V/3 A (15 W max.) Total output: 20 W max.
Efficiency	Level VI
LED Indicator	Blue
Protections	Overcharge, overcurrent, overheat, overvoltage, overload and short circuit
Operating Temperature	-10–35°C
Operating Humidity	20–80% RH (no-condensation)
Color	White
Dimensions	7.3 x 5 x 5.4 cm
Weight	110 g

Package Contents:

- » 1x Travel Adapter
- » 1x User Manual

Package Information:


» Packing Dimension: 98 x 60 x 70 mm

» Packing Weight: 0.156 kg» Carton Dimension: mm

» Carton Q'ty: pcs» Carton Weight: kg

ECE









Made in China