

Anker A1723

Anker SOLIX C300X Portable Power Station

288Wh | 300W

InfiniPower™

SurgePad™



Highlights

InfiniPower™ 10 Years of Everyday Use

LiFePO4 batteries offer a 6× longer lifespan than the average power station. Designed for a decade of daily use, with an industry-leading 5-year device warranty

140W Two-Way Fast Charging

Use the dual 140W PD 3.1 USB-C to power up two 16" Macbook Pros from 0% to 50% in just 40 minutes. Can recharge this power station to 100% within 68 minutes with ports as well.

Appliances Compact and Powerful in One

Equipped with a total 360W output and a 90,000 mAh (288Wh) battery, this unit features 8 ports (3 AC, 1 USB-A, 3 USB-C and car socket), allowing you to power multiple essential devices and tablets on the go.

UPS 10ms

Ensure continuous power with uninterruptible power supply(UPS) switchover time is under 20ms

Worry-Free Outdoor day and night

Pair up with 100W solar panels to recharge during the day, and enjoy nighttime activities with the built-in stretchable camping light, while also charging your essential devices.

Remote operation is hassle-free indoors and outdoors with Wi-Fi and Bluetooth

Using the Anker app, you can monitor and control the Anker SOLIX C300X Portable Power Station with real-time visuals and set your preferred discharge limit, battery level, recharging speed, AC timing, screen brightness, and screen time.

Specifications

Product Model

PN	A1723
Model Name	Anker SOLIX C300X Portable Power Station

Battery Info

Type of Battery	LiFePO4
Capacity	288Wh
Capacity	90000mAh
Cycle Life	3000+ (to 80%)



Specifications

Power Outputs

Maximum Output	360W
# of Output Ports	8 (For US/CA/JP) 7 (For EU/UK)
# of Standard AC Socket	3 (For US/CA/JP) 2 (For EU/UK)
AC Rated Power	300W
AC Surge Power	600W
AC Auto Shut-Off	Standby mode 2h
# of USB-A Output	1

USB-A Rated Power (per port)	5V=2.4A (12W Max)
USB-A Total Output	12W
# of USB-C Output	3
USB-C Rated Power (per port)	5V=3A (15W) 5V=3A/ 9V=3A/15V=3A/ 20V=3A/28V=5A (140W Max) 5V=3A/ 9V=3A/15V=3A/ 20V=3A/28V=5A (140W Max)
USB auto shut-off	Yes
# of Car Outlet	1
Car Outlet Rated Power (per port)	10.8~14V=10A (120W Max)

Specifications

Power Inputs

Input Voltage	100V (JP) 120V (US/CA) 230V (EU/UK)	EST DC Adapter Recharge Time :	No
Total Input Power	330W (AC Direct)	DC Input Size	XT-60
EST Recharge Time	AC recharging: 68min(330W) PD: 142mins(140W) Solar recharging: 194mins(100W)	Solar Input Power	11-28V== 8.2A(100W Max)
Use Ports While Recharging	Yes	EST Solar Recharge Time	194mins (1*100W)
Direct AC Input	Yes	Solar Panel Compatible	Yes
Maximum AC Input Power	360W	MPPT Support	Yes
# of DC Input	1		
DC Adapter	No		

Sales Market: US/CA/JP/EU/UK

Specifications

Illumination Information

Flash Light	-
Flash Light Mode	-
Ambient Light	Yes
Ambient Light Mode	Ambient Light Mode (3 Level) SOS Mode

Safety Information

Operation Temperature (°C/°F)	Charging: -20 -40°C / -4 -104°F Recharging: 0-40°C / 32-104°F
Overload Protection (AC)	>600W
Over-current Protection (USB-A)	>3A
Over-current Protection (USB-C)	>6A
Over-current Protection (Car Port)	>12.8A

Package Content

AC Adapter	-
Cable	AC Charging Cable 80cm

Weight & Dimension

Product Dimension	164*161*240mm 6.5x6.3x9.5in
Product Weight	4 kg ; 8.82 lb