

LABEL OFF

Page: 1

Compilation date: 22.07.2016

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LABEL OFF

Product code: 761.400.000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Cleaning agent / Cleaner

1.3. Details of the supplier of the safety data sheet

Company name: ECS AG

Roosstrasse 53

CH-8832 Wollerau

Switzerland

Tel: +41 (0)44 / 787 53 56

Email: gunnar.kleinmann@ecsag.com

1.4. Emergency telephone number

Emergency tel: Germany: Vergiftungs-Informations-Zentrale; +49 761 19240

Section 2: Hazards identification

2.1. Classification of the substance or mixture				
Classification under CLP: Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; Skin Irrit. 2: H315; Skin Sens. 1: H3				
	STOT SE 3: H336; Asp. Tox. 1: H304; -: H229			
Most important adverse effects:	Extremely flammable aerosol. Pressurised container: May burst if heated. Toxic to			
	aquatic life with long lasting effects. Causes skin irritation. May cause an allergic skin			
	reaction. May cause drowsiness or dizziness. May be fatal if swallowed and enters			
	airways.			

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.		H222: Extremely flammable aerosol.
		H229: Pressurised container: May burst if heated
		H411: Toxic to aquatic life with long lasting effects.
		H315: Causes skin irritation.
		H317: May cause an allergic skin reaction.
		H336: May cause drowsiness or dizziness.
		H304: May be fatal if swallowed and enters airways.
	Hazard pictograms:	GHS02: Flame
		GHS09: Environmental
		GHS07: Exclamation mark

LABEL OFF



Signal words:	Danger
Precautionary statements:	P102: Keep out of reach of children.
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
	P211: Do not spray on an open flame or other ignition source.
	P251: Do not pierce or burn, even after use.
	P273: Avoid release to the environment.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P333+313: If skin irritation or rash occurs: Get medical advice/attention.
	P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
	P501: Dispose of to.
3. Other hazards	

2.3

Other hazards: Buildup of explosive mixtures without sufficient ventilation.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

KOHLENWASSERSTOFFE, C6, ISOALKANE, <5%N-HEXAN - REACH registered number(s): 01-2119484651-34

EINECS	CAS	PBT / WEL	CLP Classification	Percent
931-254-9	-	-	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Skin Irrit. 2:	60.000%
			H315; STOT SE 3: H336	

ORANGENTERPENE - REACH registered number(s): 01-2119493353-35

232-433-8	8028-48-6	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Skin Irrit. 2:	
			Aquatic Chronic 2: H411; Skin Irrit. 2:	
			H315; Skin Sens. 1: H317	

KOHLENWASSERSTOFFE, C9-C10, N-ALKANE, ISO-ALKANE, CYCLISCHE VERBINDUNGEN, <2% AROMATEN

927-241-2	64742-82-1			15.000%
			STOT SE 3: H336; Aquatic Chronic 3:	
			H412	

LABEL OFF

	KOHLENDIOXID							
	204-696-9	124-38-9	Substance with a Community workplace exposure limit.	Press. Gas: H280	5.000%			
Sec	tion 4: First aid	measures						
4	4.1. Description of first aid measures							
	SI	kin contact:	Remove all contaminated clothes and foo	wear immediately unless stuck to skin. Wasl	า			
			immediately with plenty of soap and water	mmediately with plenty of soap and water. Consult a doctor.				
	E	ye contact:	Rinse opened eye for several minutes under running water.					
		Ingestion:	If symptoms persist consult doctor.					
		Inhalation:	In case of unconsciousness place patient	stably in side position for transportation.				
4	.2. Most importan	t symptoms	and effects, both acute and delayed					
	SI	kin contact:	Causes skin irritation.					
	E	ye contact:	Based on available data, the classification	criteria are not met.				
		Ingestion:	May be fatal if swallowed and enters airwa	ays.				
		Inhalation:	May cause drowsiness or dizziness.					
	Delayed / immedi	iate effects:	Delayed effects can be expected after long-term exposure.					
4	.3. Indication of a	ny immediat	ate medical attention and special treatment needed					
Ir	nmediate / specia	l treatment:	No further relevant information available.					
Sec	Section 5: Fire-fighting measures							
5	5.1. Extinguishing media							
	Extinguishing media: Carbon dioxide. Water spray. Dry chemical powder. Fight Larger fires with water spray or				or			
	-	-	alcohol resistant foam.					
5	.2. Special hazard	ls arising fro	m the substance or mixture					
	Exposu	ire hazards:	No further relevant information available.					
5	.3. Advice for fire	-fighters						
	Advice for f	ire-fighters:	Protective equipment: No special measure	es required. Additional information: Collect				
			contaminated fire fighting water separately	/. It must not enter the sewage system.				
Sec	tion 6: Accident	al release r	neasures					
6	.1. Personal preca	autions, prot	ective equipment and emergency proce	dures				
	Personal p	recautions:	Wear protective equipment. Keep unprote	cted persons away.				
6	.2. Environmental	precautions						
	Environmental p	recautions:	Do not allow to enter sewers/surface or gr	ound water. Inform respective authorities in				
			case of seepage into water course or sew	age system. Do not allow product to reach				
			sewage system or any water course.					

LABEL OFF

6.3. Methods and material for containment and cleaning up			
Clean-up procedures:	Dispose contaminated material as waste according to item 13. Ensure adequate		
	ventilation.		
6.4. Reference to other section	S		
Reference to other sections:	Refer to section 8 of SDS. Refer to section 13 of SDS. Safe handling: see section 7		
Section 7: Handling and stora	ge		
7.1. Precautions for safe handl	ing		
	Ensure good ventiletien/eveluation at the workplace. Keen ignition seurose every De		
nanding requirements.	Ensure good ventilation/exhaustion at the workplace. Keep ignition sources away - Do		
	not smoke. Pressurised container: protect from sunlight and do not expose to		
	temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.		
	Do not spray onto a naked flame or any incandescent material.		
7.2. Conditions for safe storag	e, including any incompatibilities		
Storage conditions:	Observe official regulations on storing packagings with pressurised containers.		
	Pressurised container: protect from sunlight and do not expose to temperatures		
	exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. Storage class:		
	2B		
7.3. Specific end use(s)			
	No further relevant information available		

Specific end use(s): No further relevant information available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

KOHLENDIOXID

Workplace exposure limits:

Respirable dust State 8 hour TWA 15 min. STEL 8 hour TWA 15 min. STEL ΕU 9100 mg/m3 --_

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and		
	contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact	
	with the eyes and skin.	
Respiratory protection:	In case of brief exposure or low pollution use respiratory filter device. Not necessary if	
	room is well-ventillated.	
Hand protection:	Protective gloves. The glove material has be impermeable and resitant to the product /	

LABEL OFF

the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Nitrile gloves. Recommended thickness of the material: >=0,4mm The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufaturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Breakthrough time of the glove material > 8 hours.
 Eye protection: Safety glasses.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties					
State:	Aerosol				
Colour:	Colourless				
Odour:	Characteristic odour				
Solubility in water:	Not miscible or difficult to mix.				
Boiling point/range°C:	Not applicable.	Melting point/range°C:	Undetermined.		
Flammability limits %: lower:	0,7 Vol%	upper:	7,4 Vol%		
Flash point°C:	-26°C	Autoflammability°C:	>200°C		
Vapour pressure:	at 20 °C: 6800 hPa	Relative density:	Not determined.		
pH:	Not applicable.	VOC g/l:	96,00 %		

9.2. Other information

Other information: Product is not selfigniting. Product is not explosive. However, formation of explosive air /

vapour mixtures are possible. Density at 20°C: 0,05g/cm3

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No further relevant information available.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: No dangerous reactions known.

10.4. Conditions to avoid

Conditions to avoid: No further relevant information available.

10.5. Incompatible materials

Materials to avoid: No further relevant information available.

10.6. Hazardous decomposition products

Haz. decomp. products: No dangerous decompsition products known.

LABEL OFF

Page: 6

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

KOHLENWASSERSTOFFE, C6, ISOALKANE, <5%N-HEXAN

DERMAL	RAT	1H LC50	>3000	mg/kg
GASES	RAT	4H LC50	>20	mg/l
ORAL	RAT	LD50	>5000	mg/kg

ORANGENTERPENE

DERMAL	RBT	LC50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

KOHLENWASSERSTOFFE, C9-C10, N-ALKANE, ISO-ALKANE, CYCLISCHE VERBINDUNGEN, <2% AROMATEN

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Causes skin irritation.

Eye contact: Based on available data, the classification criteria are not met.

Ingestion: May be fatal if swallowed and enters airways.

Inhalation: May cause drowsiness or dizziness.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

KOHLENWASSERSTOFFE, C6, ISOALKANE, <5%N-HEXAN

Daphnia magna	LC50/48h	3,87	mg/l
Oryzias latipes	LC50/48h	>1	mg/l

LABEL OFF

Page: 7

ORANGENTERPENE

DAPHNIA	48H EC50	0,67	mg/l
Pimephales promelas	96H LC50	0,7	mg/l

12.2. Persistence and degradability

Persistence and degradability: No further relevant information available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No further relevant information available.

12.4. Mobility in soil

Mobility: No further relevant information available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic for fish Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods Disposal operations: Must not be disposed together with household garbage. Do not allow product to reach sewage system. Waste code number: 15 01 10 Disposal of packaging: 15 01 04 metallic packaging Recommendation: Disposal must be made according to official regulations.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: Aerosols, Eenvironmentally hazardous

(KOHLENWASSERSTOFFE, C6, ISOALKANE, <5%N-HEXAN; ORANGENTERPENE)

14.3. Transport hazard class(es)

Transport class: 2 (5F+Gase)

LABEL OFF

	Page:	
14.4. Packing group		
Packing group:	entfällt	
14.5. Environmental hazards		
Environmentally hazardous:	Yes Marine pollutant: No	
14.6. Special precautions for us	ser	
Special precautions:	EMS Number: F-D,S-U Stowage Code: SW1, SW22 Segregation Code: SG69	
Tunnel code:		
IMDG seg. group:	LQ: 1L; EQ E0	
14.7. Transport in bulk accordi	ng to Annex II of MARPOL73/78 and the IBC Code	
Transport in bulk:	Not applicable.	
Section 15: Regulatory inform	ation	
15.1. Safety, health and environ	nmental regulations/legislation specific for the substance or mixture	
Specific regulations:	Directive 2012/18/EU Named dangerous substances - ANNEX 1 None of the ingredients	
	is listed. Seveso category:	
	E2 Hazardous to the Aquatic Environment	
	P3b Flammable Aerosols Qualifying quantity (tonnes) for the application of lower-tier	
	requirements 200 t. Qualifying quantity (tonnes) for the application of upper-tier	
	requirements 500 t.	
15.2. Chemical Safety Assessn	nent	
Chemical safety assessment:	A chemical safety assessment has not been carried out for the substance or the mixture	
	by the supplier.	
Section 16: Other information		
Other information		
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No	
	2015/830.	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	H222: Extremely flammable aerosol.	
	H225: Highly flammable liquid and vapour.	
	H226: Flammable liquid and vapour.	
	H229: Pressurised container: May burst if heated	
	H280: Contains gas under pressure; may explode if heated.	
	H304: May be fatal if swallowed and enters airways.	
	H315: Causes skin irritation.	
	HSTS. Causes skill initiation.	
	H317: May cause an allergic skin reaction.	

H412: Harmful to aquatic life with long lasting effects.

LABEL OFF

 Legal disclaimer:
 The above information is believed to be correct but does not purport to be all inclusive

 and shall be used only as a guide. This company shall not be held liable for any

 damage resulting from handling or from contact with the above product.