





airo-chemie
A. Schmiemann GmbH & Co. KG
chemisch-technische Produkte
D-40736 Langenfeld · Postfach 1143
D-40764 Langenfeld · Carl-Leverkus-Str. 27
Tel. (02173) 8538-0 · Fax 853860 + 853870

V3 1401 EN

Technical Data Sheet - Product Information

Product: **LACKSPRAY GRUNDIERUNG**

**Characteristics:**

Fast drying primer spray with high filling capacity.
Suitable for workshops for repair of worn surfaces.
Universally usable as all-purpose primer for the DIY domain.
Excellent adhesion and good protection against corrosion.
The propellant is free of CFC (chlorofluorocarbon).

Range of application:

Car-finishing, industrial and private applications

Instructions for use:

Clean surface from dust, grease and rust.
Remove loose paint layers. Old lacquer coatings should be sanded.

Prior to application shake the spray can thoroughly for at least 1 to 2 minutes.

Apply 1 to 2 layers crosswise and homogenously and keep a spray distance of 25-30 cm.

If several layers are needed allow for approx. 20 minutes flash-off time between each layer.

After a drying time of 12 hours the primer will be completely dried off and can then be coated with all lacquers commonly used in the car refinishing industry.

Drying time at 20°C	Dust free:	5 minutes
and 30 µ dry film thickness:	Tack free:	15 minutes
	Ready to sand:	30-35 minutes

Note: During application shake spray can from time to time to avoid a decrease of the spray pressure

Chemical basis:

Lackspray GRUNDIERUNG: acrylic resin, aluminium powder and solvents.
Propellant: propane / butane.

Temperature conditions:

Material and surrounding temperature should range between +18 °C and +20 °C.
Do not apply at temperatures lower than +15 °C.

Storage stability:

12 months in tightly closed tins when kept at +20 °C.

Disposal consideration:

Disposal according to local regulations.

Please consider our technical advice – be it verbally, in writing or testing and supplied to the best of our knowledge – as information only and without responsibility in respect to other parties. It does not release you from your obligation to test the products supplied regarding their suitability for the intended application. Handling and utilization of our products by the customer exceed our responsibility and are at the customer's liability. We guarantee that our products conform to their specification and we will refund or replace non conforming products only. Airo cannot be held responsible for any damages or accidents in connection with the use of our product.