

PRESENTING OUR NEWEST INNOVATION STACKABLE REEL STAND

A single Stackable Reel Stand provides storage, protection, and payout functionality for bulk cable reels. With multiple Stackable Reel Stands, users can create up to three tiers of reel storage in a compact footprint.

Choose removable casters or fork pockets to add mobility to the benefits. A steel, powder-coated frame protects contents, while angled metal guides on top bars simplify stacking.

Expand reel-handling capabilities at the jobsite or the warehouse with this flexible alternative to reel racking or jack stands.



Modular Reel Storage

Stackable Reel Stands from BHS. Inc. offer a compact, modular alternative to traditional reel racking. Adapt reel storage systems to any space by stacking up to three units high.



Flexible Reel Configuration

Compatible with wooden or metal reels, including Standard and Narrow steel reels from BHS, Inc. Configure reels to the job site requirements.



Ideal for Manual Payout

Unstacked units are suitable for paying out cable, supporting order fulfillment or jobsite installation.



Custom Options Available

Add optional, removable casters and/or fork pockets. Request custom sizes, weight capacities, and additional features.



CONTACT THE BHS SALES TEAM FOR MORE INFORMATION ABOUT THIS PRODUCT # sales@bhs1.com 1.800.BH5.9500

Flip sheet over to learn more about this electrical solution.

STACKABLE REEL STAND

WIRE & CABLE HANDLING



| Model | Max Spool Width | Max Spool Diameter | Width | Depth | Height | Capacity | Unloaded Weight |
|-----------|--------------------|-----------------------|-----------|-----------|-----------|-----------|--------------------|
| PRP-N-STK | 28" | 52" | 58.25" | 37.6875" | 55.375" | 5,000 lb | 365 lb |
| | (712 mm) | (1321 mm) | (1480 mm) | (957 mm) | (1407 mm) | (2268 kg) | (166 kg) |
| PRP-STK | 44" | 52" | 58.25" | 43.75" | 55.375" | 5,000 lb | 400 lb |
| | (1118 mm) | (1321 mm) | (1480 mm) | (1111 mm) | (1407 mm) | (2268 kg) | (181 kg) |

* Not recommended for stacking in high traffic areas. Secondary operator recommended to guide stacking. Do not attempt payout while units are stacked. Units shall not be transported while stacked.

NORTH AMERICA: P.O. Box 28990, St. Louis, MO 63132-0990 USA • 1.800.BHS.9500 • Fax: 314.423.6444 • sales@bhs1.com • BHS1.com INTERNATIONAL: P.O. Box 12429, St. Louis, MO 63132-0990 USA • +1 314 423 2075 • Fax: +1 314 423 3034 • sales@bhs1global.com Specifications are subject to change without notice. ©2023 BHS, Inc. St. Louis, MO. Data Sheet: PL-12400 03/23