



PRESENTING OUR NEWEST INNOVATION **LIFT TABLE LADDER**

The Lift Table Ladder from BHS, Inc. provides access to high shelves along with an integrated material lift, improving safety and efficiency for stocking and retrieval tasks. Users roll the unit into place via phenolic casters. They climb the steel, anti-skid steps to a fixed-height work platform. There, they control the electric-powered lift carriage with a push-button pendant, safely lifting and lowering materials. This design eliminates ergonomic and fall risks, while simplifying access to high shelves. Choose custom heights to match shelving elevation.



Integrated Work Platform & Material Lift

Eliminate the risks associated with carrying boxes up and down ladders. This warehouse solution combines a ladder, work platform, and material lift into a single unit for working at height.



Built for Safety

Anti-skid tape prevents slips on both the operator platform and steps. A steel guard protects operators from the lift track, while electrical components are located inside the frame.



Heavy Duty Construction

Solid steel materials provide durability, while a powder-coat finish protects the unit from spills and corrosion.



Custom Models for Any Use Case

Specify your required height, size, and carrying capacities. Additional features are available on request.

CONTACT THE BHS SALES TEAM FOR MORE INFORMATION ABOUT THIS PRODUCT

Flip sheet over to learn more about this warehouse solution. sales@bhs1.com [1.800.BHS.9500](tel:1.800.BHS.9500)

LIFT TABLE LADDER

WORK PLATFORM



Operator Protection

Steel operator guard prevents contact with lift track

Boost Worker Safety

Reduces both ergonomic and fall risks



Powered Elevation

Powered lift capability for high-shelf stocking and retrieval features a 450 lb (204 kg) load capacity

Effortless Work Positioning

The yellow carriage lifts and lowers materials from a range of 17.5" to 108" high (445 mm to 2743 mm)



Heavy Duty Construction

Solid steel construction on steps and operator platform include anti-skid tape to prevent slipping

Smooth Mobility

2 rigid and 2 swivel phenolic casters for single-operator maneuvering



Simple Controls

Simple, push-button pendant for battery-powered operation. Magnet-back allows pendant to store anywhere on the frame

Customizable

Custom heights, capacities, and features available. Contact a BHS Representative to discuss your requirements.



Safety Brake

Locking floor brake prevents unwanted movement of the ladder

Model	Overall Length	Overall Width	Overall Height	Operator Platform (W x D x H)	Ladder Capacity	Carriage Dimension (W x D x H)	Carriage Capacity
LTL-2034-108	98.9375" (2513 mm)	34.625" (879 mm)	118.125" (3000 mm)	30.375" x 37.375" x 68.125" (772 mm x 949 mm x 1730 mm)	250 lb (113 kg)	34.375" x 20.25" x 1.5" (873 mm x 514 mm x 38 mm)	450 lb (204 kg)

Note: Do not move unit with riders or with load on carriage.