



# PRESENTING OUR NEWEST INNOVATION CONDUIT CARRIER CART

Transport bulk loads of electrical conduit with the Conduit Carrier Cart, a material-handling cart designed specifically to remove hazards and productivity losses associated with moving this component.

# **Deliver Conduit Loads to the Precise Point of Installation**

The closer electrical materials are to the installation point, the quicker the work gets done. Conduit Carrier Carts offer ergonomic push grips and easy-rolling, locking casters to save time on the job. Carts are available with load capacities of 3,000 pounds, 5,000 pounds, and more.



# Handles All Types of Conduit

Load standard lengths of metal conduit, electrical metallic tubing, or rigid PVC conduit for simpler, safer transportation across job sites.



# Choose a Model to Fit Your Job Site

Ultra-slim units are just 19 inches wide, to easily fit through narrow aisles and standard door frames. Or choose a high-capacity, highvolume model for bigger jobs.



# **Steel Tie-Down Plates Secure Loads**

Two steel, powder-coated tie-down plates are welded directly to the frame. Secure loads with straps for stability during storage and movement.



## **Heavy-Duty Steel Construction**

Conduit Carrier Carts are precision-welded with steel square tubing to withstand the rigors of construction sites. The powder-coat finish resists damage from chemicals, abrasions, and impacts.

CONTACT THE BHS SALES TEAM FOR MORE INFORMATION ABOUT THIS PRODUCTFlip sheet over to learn more about this electrical solution.Image: Image: Imag

# **CONDUIT CARRIER CART** ELECTRICAL MATERIAL CARTS

Please note: All specs called out below apply to CC-3K & CC-5K unless a different model is specifically called out

#### **Custom Laser-Cut Logo**



Take your brand onto the jobsite with custom laser logos

#### **Ergonomic Handles**

The CC-3K & CC-5K are equipped with 2 push handles on both sides for simplified positioning

#### **Secure Materials**

Two steel tie-down plates for strapping and securing a load

### Capacity

Conduit Carrier Carts can carry 1,500 lb to 6,000 lb of electrical materials depending on selected model

#### Move Large Loads with High Capacity Models



Both 6K models of the Conduit Carrier Cart (CC-6K-24060 & CC-6K-46240) attach to a forklift for simplified bulk conduit transport

## For Simplified Elevator Usage Try Alternate Model



and out of elevators as well as standard doorways

Mobility

All Conduit Carrier Carts are available with casters, ensuring that conduit can be moved throughout your facility or jobsite to places forklifts cannot reach. CC-3K & CC-5K feature larger caster in center of unit for easy swiveling.

#### **Enclosed Conduit Storage Available**



Lock your conduit in our Will Call Dropbox (HVC-DB-CB) for added security

Model	Capacity	Depth	Width	Height	Casters
CC-1.5K-6040	1,500 lb / 680 kg	64" 1626 mm	44" 1118 mm	94/118" 2388/2997 mm	<ul><li>(2) Quick disconnect 8" / 203 mm rigid phenolic,</li><li>(2) Quick disconnect 6" / 152 mm swivel phenolic</li></ul>
CC-3K-6032	3,000 lb / 1361 kg	66.5" 1689 mm	32" 813 mm	47" 1194 mm	(2) Quick disconnect 8" / 203 mm rigid phenolic, (2) Quick disconnect 6" / 152 mm swivel phenolic
CC-5K-6032	5,000 lb / 2268 kg	66.5" 1689 mm	32" 813 mm	47" 1194 mm	(2) Quick disconnect 8" / 203 mm rigid phenolic, (2) Quick disconnect 6" / 152 mm swivel phenolic
CC-5K-7218	5,000 lb / 2268 kg	78.5" 1994 mm	19" 483 mm	47" 1194 mm	(2) Quick disconnect 8" / 203 mm rigid phenolic, (2) Quick disconnect 6" / 152 mm swivel phenolic
CC-6K-24060	6,000 lb / 2722 kg	240" 6096 mm	60" 1524 mm	39.5" 1003 mm	(3) 8" / 204 mm swivel poly casters
CC-6K-24046	6,000 lb / 2722 kg	240" 6096 mm	48.5" 1232 mm	25" 635 mm	

**NORTH AMERICA:** P.O. Box 28990, St. Louis, MO 63132 USA • 1.800.BHS.9500 • Fax: 314.423.6444 • sales@bhs1.com • BHS1.com **INTERNATIONAL:** P.O. Box 12429, St. Louis, MO 63132 USA • +1 314 423 2075 • Fax: +1 314 423 3034 • sales@bhs1global.com Specifications are subject to change without notice. ©2019-2023 BHS, Inc. St. Louis, MO. Data Sheet: PL-8400 09/23